



Connectors > Contacts > Connector Contacts



Contact Type: **Pin**
Contact Mating Area Plating Material: **Precious Metal**
Wire Contact Termination Area Plating Material: **Gold Flash**
Contact Retention Within Housing: **With**
Contact Retention Type Within Housing: **Spring**

Features

Product Type Features

Discrete Wire Type	Solid or Stranded
Sealable	No

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Contact Features

Contact Underplating Material	Nickel
Contact Orientation	Straight
Mating Pin Diameter	1.57 mm[.062 in]
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Length	26.75 mm[1.053 in]
Wire Contact Termination Area Plating Thickness	1.27 µm[50 µin]
Barrel Type	Open



Contact Type	Pin
Contact Mating Area Plating Material	Precious Metal
Wire Contact Termination Area Plating Material	Gold Flash
Contact Retention Within Housing	With
Contact Size	Size 16
Contact Base Material	Copper Nickel Alloy
Contact Current Rating (Max)	25 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Contact Retention Type Within Housing	Spring

Dimensions

Compatible Insulation Diameter Range	2.79 – 3.81 mm[.11 – .15 in]
Wire Size	.8 – 2 mm²

Usage Conditions

Operating Temperature Range	-55 – 150 °C[-67 – 302 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Quantity	4000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247)



	Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1977878-1 SLD CPC PLUG ASY,11-4,STD SEX, UV RESIST	 TE Part # 200893-2 INSERTION TOOL CONT	 TE Part # 206516-1 CPC PLUG ASSEMBLY SIZE 11-4	 TE Part # 208716-1 CMC PLUG ASSEMBLY,SZ 14
 TE Part # 213853-1 CPC PLUG ASSEMBLY SIZE 23-19	 TE Part # 213849-1 CPC PLUG ASSEMBLY SIZE 17-16	 TE Part # 208718-2 CMC PLUG ASSEMBLY,SZ 14-5	 TE Part # 211770-2 CPC PLUG ASSEMBLY SIZE 23-19
 TE Part # 796274-1 SLD CPC PLUG ASSY,17-16,STD SX	 TE Part # 7-2151405-7 OCEAN_2.0_SPARE_PART_KIT-090F155O	 TE Part # 796274-2 SLD CPC PLUG ASSY,17-16,STD SX	 TE Part # 796188-1 SLD CPC PLUG ASSY,23-24,STD SX



TE Part # 796271-1
SLD CPC PLUG ASSY,17-14,REV SX



TE Part # 91521-1
CCII TYPE III+ PIN SKT 18-14 ASSY



TE Part # 206708-1
CPC PLUG ASSEMBLY SIZE 13-9



TE Part # 208718-1
CMC PLUG ASSEMBLY,SZ 14-5



TE Part # 208470-1
CMC PLUG ASSEMBLY,SZ 28



TE Part # 211400-1
CPC PLUG ASSEMBLY SIZE 13-7



TE Part # 213848-1
CPC PLUG ASSEMBLY SIZE 23-37



TE Part # 211768-1
CPC PLUG ASSEMBLY SIZE 17-9

Also in the Series | AMP Type III+



Connector Contacts(260)



Insertion & Extraction Tools(4)



Power Contacts(260)

Also in the Series | Circular Plastic Connectors Series 1



Circular Power Connectors(211)



Connector Contacts(260)



Power Contacts(260)

Customers Also Bought



TE Part #1969812-1
06P UMNLR HDR ASSY R/A, PIN V0 GW



TE Part #535074-1
EURO SHROUD 96 POS



TE Part #1-794612-0
PIN CONT 20-24 TIN PLATE L/P




TE Part #66741-9
TYPE XII FEMALE CONT (STRIP)



TE Part #102107-2
MOD IV PIN LP



TE Part #170362-3
MINI UNIVERSAL M-N-L SOCKET



TE Part #5207908-4
STRAIN REL W/SCREW RET KIT



TE Part #66597-8
III+ PIN,18-14,TIN ,STRIP



TE Part #1445049-2
FREE HANG SNGL ROW HSG 2 POS



TE Part #745254-2
20DF PIN CONTACT,PLATED

Documents

Product Drawings

III+ PIN,18-14,30AU/FL,STRIP

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-66597-0_AA.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-66597-0_AA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-66597-0_AA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



AMP Circular Connectors for Commercial Signal & Power Applications

English

Signal Contacts

English

Product Specifications

Product Specification

English