




Connectors > Contacts > Connector Contacts



Contact Type: **Pin**
Contact Mating Area Plating Material: **Gold (Au)**
Wire Contact Termination Area Plating Material: **Tin**
Operating Voltage: **600 VDC**

Features

Product Type Features

Discrete Wire Type	Stranded
--------------------	----------

Electrical Characteristics

Operating Voltage	600 VDC
-------------------	---------

Contact Features

Contact Underplating Material	Nickel
Contact Orientation	Straight
Mating Pin Diameter	1 mm[.039 in]
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]
Wire Contact Termination Area Plating Material Finish	Bright
Wire Contact Termination Area Plating Thickness	2.54 µm[100 µin]
Contact Type	Pin
Contact Mating Area Plating Material	Gold (Au)
Wire Contact Termination Area Plating Material	Tin
Contact Retention Within Housing	With



Contact Base Material	Brass
Contact Current Rating (Max)	11.2 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Compatible Insulation Diameter Range	1.5 – 2.39 mm[.059 – .094 in]
Wire Size	.3 – .9 mm²

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	4500
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1-172233-6 2 POS MINI UNIV FREE HANG BLUE	 TE Part # 172340-1 MINI UMNL PLUG HOUSING 9P	 TE Part # 1445510-1 REC,8-3,FRE HNG,SM INS,STD KEY	 TE Part # 1445822-3 REC,11-7,FLNG MT,LG INS,STD KE
 TE Part # 172233-1 2 POS MINI UMNL CAP HOUSING	 TE Part # 7-2266248-7 OC-062F110F-752-CRIMPTOOLINGKIT	 TE Part # 172337-1 MINI UMNL PLUG HOUSING 3P	 TE Part # 1-172168-2 MINI UNIVERSAL M-N-L PLUG 6P
 TE Part # 1-172157-2 2CIR MINI U-M-N-L CAP RED	 TE Part # 770580-1 10P MINI UMNL PLUG HSG	 TE Part # 172336-1 2P MINI UMNL PLUG HOUSING	 TE Part # 770583-1 16P MINI UMNL PLUG HSG



TE Part # 172170-1
12 CIR UNIV M-N-L PLUG

TE Part # 172161-1
9 CIR UNIV M-N-L CAP

TE Part # 1445537-3
REC,8-3,FLNG MT,LG INS,STD KEY

TE Part # 1445807-1
PLUG,11-9,SM INS,STD KEY

TE Part # 1445807-3
PLUG,11-9,LG INS,STD KEY

TE Part # 1445538-3
REC,8-2,FLNG MT,LG INS,STD KEY

TE Part # 1445827-1
REC,11-7,FRE HNG,SM INS,STD KE

TE Part # 1445818-3
PLUG,11-7,LG INS,STD KEY

Also in the Series | Mini-Universal MATE-N-LOK

Connector Caps & Covers(2)

Connector Contacts(89)

Connector Hardware(4)

Connector Seals & Cavity Plugs(17)

Connector Strain Relief(2)


Insertion & Extraction Tools(1)

PCB Headers & Receptacles(93)

Rectangular Power Connectors(196)

Wire-to-Board Headers & Receptacles
(93)

Customers Also Bought



TE Part #521119-1
PL 250 HOUSING RECEPTACLE
NYLON 6/6



TE Part #5-103957-8
2X9 MTE RCPT SR LATCH .100CL



TE Part #794758-1
MINI UMNL WIRE SEAL,18-26AWG




TE Part #2320920-1
AS16,PLUG ASSY,HT,02P,N SEAL,
CODE A




TE Part #5-103957-6
2X7 MTE RCPT SR LATCH .100CL



TE Part #1-794608-2
PIN CONT 20-24 30 GOLD STRIP



TE Part #796638-3
3POS 5.08MM CE R/A HDR,TRM BLK



TE Part #796638-5
5POS 5.08MM CE R/A HDR,TRM BLK



TE Part #2320913-1
AS16,CAP ASSY,HT,02P,N SEAL,
CODE A



TE Part #794772-2
02P MINI UMNL SEAL,DIE CUT

Documents

Product Drawings

MINI UMNL PIN 22-18 AWG AU

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-770903-0_U.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-770903-0_U.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-770903-0_U.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



AMP Circular Connectors for Commercial Signal & Power Applications Continued

English

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English