Positive Lock | Positive Lock 250

TE Internal #: 1-926522-2

TE Internal Description: PL 250 REC HSG 2P NYLON NAT

View on TE.com >



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings









Cable Mount (Free-Hanging)



Terminal Type: Receptacle

Connector & Housing Type: Receptacle

Number of Positions: 2

Terminal Orientation: Straight
UL Flammability Rating: UL 94V-0

Features

Product Type Features

Product Type Features	
Sealable	No
Connector & Housing Type	Receptacle
Configuration Features	
Number of Positions	2
Body Features	
Primary Product Color	Natural
Contact Features	
Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without
Mechanical Attachment	
Mating Alignment	With

Connector Mounting Type



Housing Material	Polyamide
Centerline (Pitch)	7.4 mm[.291 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | Positive Lock 250





Automotive Terminals(1)




Crimp Terminal Housings(177)



Insertion & Extraction Tools(3)




Insulation Boots & Sleeves(5)




Customers Also Bought




TE Part #1717677-2 CAP ASSY,12P,BRACKET REVERSE TYPE,ATAC C



TE Part #171661-1 E-J MK-2 070 TAB CONT



TE Part #3-520132-2 ULTRAFAST 250 ASSY FLAG REC 16-14 TPBR



TE Part #174264-2 ECONO-J MK-2 CAP HSG 6P



TE Part #DT-RT1
EXT TOOL, FRONT RELEASE



TE Part #HDP24-24-35PN-L017 REC, 35P, BLK, N, RNG, 16/20, P




TE Part #917308-1
MINI MLC CONN REC CONT.



TE Part #6-1393246-9 W23-X1A1G-25=W23/W31-



TE Part #DT4P-BT
BOOT, 4P, REC, ST, GRY



TE Part #HDC16-9-JDL

DUST CAP, 9P, REC, GRY, LANYARD,

HD10

Documents



Product Drawings

PL 250 REC HSG 2P NYLON NAT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-926522-2_R.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-926522-2_R.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-926522-2_R.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals

UL Report

English