

## Z-PACK | Z-PACK 2mm HM

TE Internal #: 100143-1

Hard Metric Backplane PCB Mount Header, ≤1 Gb/s, 25 Column, 5 Row, Mezzanine, 125 Position, 2 mm [.078 in] Centerline, Vertical,


Gray, Z-PACK 2mm HM

View on TE.com >




Connectors > PCB Connectors > Backplane Connectors > Hard Metric Backplane Connectors >

Hard Metric Male Connector: Traditional Backplane, Mezzanine, 2mm











PCB Connector Type: PCB Mount Header

Data Rate: ≤1 Gb/s
Number of Columns: 25

Number of Rows: 5

Backplane Architecture: Mezzanine

All Hard Metric Male Connector: Traditional Backplane, Mezzanine, 2mm (124)

## **Features**

## **Product Type Features**

Connector & Contact Terminates To	Printed Circuit Board
Backplane Interface Type	2mm HM
Connector System	Board-to-Board
PCB Connector Type	PCB Mount Header
Sealable	No

## **Configuration Features**

Rows Loaded	A, B, C, D, E
Number of Columns	25
Number of Rows	5
Backplane Architecture	Mezzanine
Number of Positions	125
PCB Mount Orientation	Vertical



# Signal Characteristics

Crosstalk Version	Standard
Data Rate	≤1 Gb/s

# **Body Features**

Primary Product Color	Gray	

#### **Contact Features**

Contact Underplating Material	Nickel
Contact Mating Area Length	13.45 mm
Contact Base Material	Phosphor Bronze
CompactPCI Designation	None
PCB Contact Termination Area Plating Material	Tin-Lead
Feedthrough Post Length	3.7 mm
Contact Type	Pin
Contact Mating Area Plating Material	Gold (Au)
Contact Mating Area Plating Material Thickness	.8 μm[31.5 μin]
Contact Current Rating (Max)	1.5 A

#### **Termination Features**

Termination Method to PCB	Through Hole - Press-Fit

# Mechanical Attachment

Connector Mounting Type	Board Mount
Mating Alignment Type	Multi-Purpose Center
Front Mating Level	Level 1

# **Housing Features**

Housing Material	PBT GF
Centerline (Pitch)	2 mm[.078 in]

#### **Dimensions**

# **Usage Conditions**

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
operating remperature name	00 120 0[ 07 207 1 ]

# Operation/Application

Shi	elded	No	



Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	10
Packaging Method	Tube

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (13% in 4690948374) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Also in the Series | Z-PACK 2mm HM



Board-to-Board Headers & Receptacles(46)



Connector Contacts(2)



Connector Hardware(91)



Hard Metric Backplane Connectors (266)



Power Contacts(2)



Rectangular Power Connectors(46)

# Customers Also Bought



TE Part #5-104363-7
08 MTE HDR SRST LATCH .100CL



TE Part #2-2176308-2 RP 1E 0.1W 221K 0.1% 25PPM 5K RL




TE Part #100147-1 Z-PACK/A F-HDR.110P



TE Part #5-103168-5 14 MODII HDR DRST SHRD .100CL





TE Part #1-794066-0 12P MINI UMNL HDR W/DH SN LF



TE Part #5-534206-7 14 MODII VRT DR CE 100/115



TE Part #5-5179009-1 0.8FH,R09H.5,040,08/Sn,TU







## **Documents**

## **Product Drawings**

PACK/A MALE HDR 110P, 2MM HM

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_100143-1\_K.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_100143-1\_K.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_100143-1\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

Stacking Connectors Quick Reference Guide (English)

English

# **Product Specifications**

**Application Specification** 

English

#### **Instruction Sheets**

INSERTION TOOL FOR Z-PACK 2mm HM CONN.

Japanese

Instruction Sheet (non U.S.)

Japanese