




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.31 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.64 mm [.025 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.64 mm[.025 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Product Length	19.18 mm[.755 in]
Compatible Insulation Diameter Range	2.29 – 3.3 mm[.09 – .13 in]
Terminal Material Thickness	.3 mm[.012 in]
Wire Size	.51 – 1.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



KIT

REPRESENTATION ONLY

TE Part # 7-2150186-7
[OCEAN_2.0_SPARE_PART_KIT-090F180F](#)



TE Part # 936663-1
[PL 187 REC 20-16 AWG 0.3 X 14.0 PTPBR](#)



TE Part # 2150186-2
[OCEAN_2.0_Applicator-E-090F180F-REA](#)



TE Part # 2825431-1
[187 SERIES POSITIVE LOCK \(MARK-II\) REC](#)




TE Part # 2150186-1
[OCEAN_2.0_Applicator-E-090F180F-REM](#)



TE Part # 190679-2
[POSILOK T'P](#)

Also in the Series | Positive Lock 187



[Crimp Terminal Housings\(76\)](#)



[Insertion & Extraction Tools\(2\)](#)



[Insulation Boots & Sleeves\(7\)](#)



[Quick Disconnects\(57\)](#)

Also in the Series | Mark II



Automotive Connector Locks & Position Assurance(1)




Automotive Housings(6)



Automotive Terminals(3)



Connector Seals & Cavity Plugs(1)



Crimp Terminal Housings(76)



Insertion & Extraction Tools(2)




Quick Disconnects(57)


Customers Also Bought



TE Part #2-480435-3
187 FASTON HSG.,REC.,1 POS,BLACK



TE Part #2-520193-2
ULTRA-FAST 187 ASY REC 22-18 TPBR



TE Part #175179-1
187 PL MII TAB. 22-16 AWG PTBR



TE Part #172761-1
PL 250 FLAG REC 18-22 0.40 X 49.2 PTBR



TE Part #NB11784001
ATUM-8/2-0-SP



TE Part #324993
TERMINAL,PIDG R 16-14 2



TE Part #170265-4
PL 250 REC 12-10 AWG 0.406 X 42.3 TPPHBZ



TE Part #63832-2
187 FASTON REC 18-14 AWG TPBR



TE Part #2299282-1
POD-LOK 250 STR. AWG 22-18 PTPBR GF



TE Part #2299286-1
POD-LOK 187 STR. AWG 24-20 PTPBR GF

Documents



Product Drawings

PL 187 TERMINAL REC 20-16 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1217580-1_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1217580-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1217580-1_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL

English