

AMP | Junior Power Timer

TE Internal #: 1355390-1


2 Position Housing, Housing for Female Terminals, Wire-to-Wire, 5 mm [.197 in] Centerline, Black, Wire & Cable, Power, Junior Power

Timer

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Number of Positions: 2

Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 2.8 mm [.11 in] Connector System: Wire-to-Wire Centerline (Pitch): 5 mm [.197 in]

All Timer Connector Housing (437)

Features

Product Type Features

| Mixed & Hybrid Connector | No | | |
|-----------------------------------|------------------------------|--|--|
| Connector Shape | Rectangular | | |
| Connector & Housing Type | Housing for Female Terminals | | |
| Connector System | Wire-to-Wire | | |
| Sealable | No | | |
| Primary Locking Feature | On the Terminal | | |
| Connector & Contact Terminates To | Wire & Cable | | |
| Configuration Features | | | |
| Number of Positions | 2 | | |
| Number of Rows | 1 | | |
| Electrical Characteristics | | | |
| Operating Voltage | 12 VDC | | |
| Nominal Voltage Architecture | 12 V | | |
| Body Features | | | |
| Cable Exit Angle | 180° | | |
| Primary Product Color | Black | | |



Contact Features

| Contact Size | 2.8mm |
|------------------------------|----------------|
| Contact Type | Receptacle |
| Mating Tab Width | 2.8 mm[.11 in] |
| Contact Current Rating (Max) | 30 A |

Mechanical Attachment

| Strain Relief | Add By Accessory |
|-----------------------------|----------------------------|
| Terminal Position Assurance | No |
| Mating Alignment Type | Polarization |
| Mating Alignment | With |
| Connector Mounting Type | Cable Mount (Free-Hanging) |

Housing Features

| Housing Material | PA |
|--------------------|---------------|
| Centerline (Pitch) | 5 mm[.197 in] |

Dimensions

| gth . | 11.4 mm[.449 in] | |
|-------|------------------|--|
| jth . | 11.4 mm[.449 in] | |

Usage Conditions

| Operating Temperature (Max) | 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C[158 °F][167 °F][176 °F][185 °F] [194 °F][212 °F][221 °F][230 °F] |
|-----------------------------|--|
| Operating Temperature Range | -40 - 110 °C[-40 - 230 °F] |

Operation/Application

| Circuit Application | Power | |
|---------------------|-------|--|
| Industry Standards | | |

industry Standards

| UL Flammability Rating | UL 94V-2 |
|------------------------|----------|
|------------------------|----------|

Packaging Features

| | Packaging Method | Carton |
|---|------------------|--------|
| 0 | ther | |
| | | |

Serviceable Yes Connector Position Assurance Capable No

Product Compliance

For compliance documentation, visit the product page on TE.com>



| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts








Also in the Series | Junior Power Timer





Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(8)



Automotive Housings(279)



Automotive Terminals(150)



Busbars & Terminals(1)




Connector Seals & Cavity Plugs(7)



Module Components(1)



Other Automotive Connector Accessories(2)



Special Purpose Terminals(2)


Customers Also Bought



TE Part #TCD14741111-020 M12D4-MS-RJ-PVC-22SH-TYPE B GREEN-2.0M



TE Part #1379668-2 24W PLUG HSG ASSY grey



TE Part #2434749-1 12POS,MQS,REC HSG,COD A





TE Part #CAT-M9194-CH8172 MULTILOCK, CONNECTOR HOUSING





Documents



Product Drawings

JUN-POW-TIM GEH 2P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1355390-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1355390-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1355390-1_A.3d_stp.zip

English

Customer View Model

ENG_CVM_1355390-1_A4.3d_igs.zip

English

Customer View Model

ENG_CVM_1355390-1_A4.3d_stp.zip

English

Customer View Model

ENG_CVM_1355390-1_A4.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.