




Connectors > Pluggable IO Connectors & Cages > SFP Connectors



Form Factor: **SFP**

Pluggable I/O Product Type: **Cage Assembly**

Sealable: **No**

Circuit Application: **Signal**

Operating Temperature Range: **-55 – 85 °C [-67 – 185 °F]**

[All SFP Connectors \(10\)](#)

Features

Product Type Features

Cage Type	Single
Thermal Accessory Type Included	Heat Sink
Form Factor	SFP
Pluggable I/O Product Type	Cage Assembly
Sealable	No

Configuration Features

Number of Positions	20
Number of Ports	1
Port Matrix Configuration	1 x 1

Electrical Characteristics

Data Rate (Max)	4 Gb/s
-----------------	--------

Body Features

Heat Sink Style	Pin
-----------------	-----



.165 in

Heat Sink Height Class	PCI
------------------------	-----

Termination Features

Termination Method to PCB	Through Hole - Press-Fit
Termination Post & Tail Length	3 mm[.118 in]

Housing Features

Cage Material	Copper Alloy
---------------	--------------

Dimensions

PCB Thickness (Recommended)	2.25 mm[.089 in]
-----------------------------	------------------

Usage Conditions

Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Pluggable I/O Applications	SFP
Heat Sink Compatible	Yes
Circuit Application	Signal

Packaging Features

Packaging Method	Box & Tray
------------------	------------

Other

Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2215084-4
ASSY, SEATING TOOL, SFP 1X1

TE Part # 1367147-1
SFP COVER, UNPLATED

TE Part # CAT-SF59-C76264
SFP Connectors

TE Part # 1761394-1
DUST COVER, SFP, GANGED & STACKED

TE Part # 1367147-3
SFP COVER, UNPL, NO LOGO

Also in the Series | DWDM

Pluggable IO Connectors & Cages(4)

SFP, SFP+ & zSFP+(4)

Customers Also Bought






TE Part #1658621-9
40 NOVO MIL/CTR 15DP,LEAD FREE



TE Part #2-406549-1
IMJ,1X1,PNL GRD,LED(G/Y), SN



TE Part #640456-4
04P MTA100 HDR ASSY F/L SQ STR



TE Part #214787-E
EPSVA KS GDM4 EE 6 3,8 SN *
STROMVERSORG



TE Part #3-1761603-3
IDC LOW PRO HDR 40P VERT BLUE



TE Part #203346-E
MJIM IMV 1X1 S 810 * X R THRU * L9A
M5B0



TE Part #6469083-1
HMZD 3PAIR, HDR ASSY, 25MM MOD



TE Part #499786-9
040 UNIV HDR RA 4S 15DP STD L1



TE Part #3-640599-2
02P MTA156 CONN ASSY 18AWG
ORA

Documents

Product Drawings

DWDM Kit Assy, PCI (4.2)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1367645-4_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1367645-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1367645-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Product Specification

English