




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.34 – .75 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	16.1 mm[.634 in]
Compatible Insulation Diameter Range	1.5 – 2.5 mm[.059 – .098 in]
Terminal Material Thickness	.25 mm[.01 in]
Wire Size	.34 – .75 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Other

Line	Premier
------	---------

Product Compliance

For compliance documentation, visit the product page on TE.com>





EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 151614-2 110 MINI FASTON, REC., 24-20 AWG, BR	 TE Part # 2150049-1 OCEAN-2.0-APPLICATOR-E-062F090F-REM	 TE Part # 2150636-1 OCEAN-2.0-APPLICATOR-E-062F090OV-REM	 TE Part # 7-2150049-7 OCEAN_2.0_SPARE_PART_KIT-062F090F
 TE Part # 7-2150636-7 OCEAN_2.0_SPARE_PART_KIT-062F090OV	 TE Part # 2150049-2 OCEAN-2.0-APPLICATOR-E-062F090FA-REA	 TE Part # 737107-1 110 FASTON REC 20-17 AWG BR	 TE Part # 2063846-1 CCII 110 FASTON REC 24-18 ASSY
 TE Part # 160597-4 110 FASTON, REC., 30-26 AWG, TPBR	 TE Part # 2150636-2 OCEAN-2.0-APPLICATOR-E-062F090OV-REA		

Also in the Series | FASTON 110



Crimp Terminal Housings(13)



Insertion & Extraction Tools(1)



PCB Terminals(22)



Quick Disconnects(164)

Customers Also Bought




TE Part #280050-7
250 FASTON,FLAG,REC.,16-20 AWG, TPPB




TE Part #9231513001
100G1141-1.00-0/2/6/9-0



TE Part #90760-1
PROCrimp TL W/DIE MIN UNIV MNL



TE Part #5-1452013-1
MQS0,63 Au rec LL unseal. 0,5-0,75




TE Part #282019-049
44A0111-18-9



TE Part #1-88997-2
FFC S.TAB 100SN RL




TE Part #58637-1
PRO-CRIMP TL & DIE 20-14 UMNL



TE Part #3-770565-2
MINI AMP-IN 22-18 AWG LF



TE Part #1-1418775-1
5POS MQS REC



TE Part #3-640108-1
AMP-IN, MINI 26-22 008PTLPHBZ

Documents

Product Drawings

110 FASTON,REC.,22-18 AWG,PTBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_140717-2_AS.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_140717-2_AS.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_140717-2_AS.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Wire Preparation And Crimp Inspection Guide](#)

English

Agency Approvals

[Agency Approval Document](#)

English