

Agastat | Agastat GP Series

TE Internal #: 1423156-6

General Purpose Signal Relay, AC, Monostable, 4 Form C 4PDT-CO, 10 A Contact Rating, 120 VAC Coil Voltage, 120 VAC Contact

Voltage, Agastat GP Series

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Signal Relay

Current Type: AC

Coil Magnetic System: Monostable

Contact Arrangement: 4 Form C 4PDT-CO

Contact Current Rating: 10 A

Features

Product Type Features

Product Type Features	
Relay & Contactor Type	General Purpose Signal Relay
Configuration Features	
Contact Number of Poles	4
Contact Arrangement	4 Form C 4PDT-CO
Electrical Characteristics	
Input Voltage	120 VAC
Coil Power Rating AC	6 VA
Contact Switching Voltage (Max)	120 VAC
Contact Current Rating	10 A
Coil Voltage Rating	120 VAC
Contact Voltage Rating	120 VAC
Mechanical Attachment	
Product Mount Type	Socket Mount
Dimensions	
Product Width	45 mm[1.77 in]

45 mm[1.77 in]

109 mm[4.29 in]

Product Length

Product Height



Usage Conditions

Operating Temperature Range	0 – 60 °C
Environmental Ambient Temperature (Max)	60 °C[140 °F]
Operation/Application	
Indicator Type	LED
Current Type	AC
Coil Magnetic System	Monostable

Packaging Features

Fackaging ivietnod box & Carton	Packaging Method	Box & Carton
---------------------------------	------------------	--------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Also in the Series | Agastat GP Series





Customers Also Bought















Documents

Product Drawings
GPIQ=RLY,120VAC,LED

English

Datasheets & Catalog Pages 5-1773450-5_sec12_GP_ML_TR

English

General Purpose Signal Relay, AC, Monostable, 4 Form C 4PDT-CO, 10 A Contact Rating, 120 VAC Coil Voltage, 120 VAC Contact Voltage, Agastat GP Series

