# 031-0024-0001 ACTIVE



#### Microdot

TE Internal #: 1467939-1

SMB Connector, Receptacle, 50 ohm, Threaded, 1 Position,


Sealable, Wire & Cable, Panel Mount, -55 – 125 °C [-67 – 257 °F],

Solder Lug / Solder Pot

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMB

RF Connector Style: Receptacle

RF Connector Mated Outer Diameter (Approximate): 4.75 mm [ .187 in ]

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Threaded

### **Features**

### **Product Type Features**

Connector Seal & Plug Type	Gasket
Connector Shape	Circular
Connector Product Type	Connector Assembly
RF Interface	SMB
RF Connector Style	Receptacle
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable

## **Configuration Features**

Number of Positions	1
Number of Coaxial Contacts	1

### **Electrical Characteristics**

Impedance	50 Ω	

# **Body Features**

Cable Connector Orientation	Straight
Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Silver

## **Contact Features**



RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Method to Wire & Cable	Solder Lug, Solder Pot
Mechanical Attachment	
Panel Mount Feature Type	Jam Nut
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Screw
Dimensions	
Panel Thickness (Recommended)	3.05 mm[.12 in]
RF Connector Mated Outer Diameter (Approximate)	4.75 mm[.187 in]
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Packaging Features	
Packaging Method	Package
Other	
Grade	Commercial
Dielectric Material	PTFE

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)  Candidate List Declared Against: JAN 2025 (247)  SVHC > Threshold:  Pb (3.7% in 74019106)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR



#### /CFR/PVC Free

### Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Customers Also Bought













### **Documents**

### **Product Drawings**

SMB Connector, Receptacle, 50 ohm, Threaded, 1 Position, Sealable, Wire & Cable, Panel Mount, -55 – 125 °C [-67 – 257 °F], Solder Lug / Solder Pot



### 031-0024-0001

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1467939-1\_P.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1467939-1\_P.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1467939-1\_P.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.