




Connectors > Automotive Connectors > Automotive Housings > TH/.025 CONNECTOR SYSTEM, HOUSING



Number of Positions: 12

Connector & Housing Type: **Housing for Male Terminals**

Mating Tab Width: .64 mm [.025 in]

Connector System: **Wire-to-Wire**

Centerline (Pitch): 2.2 mm [.087 in]

[All TH/.025 CONNECTOR SYSTEM, HOUSING \(168\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	No
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	12
Number of Rows	2

Electrical Characteristics

Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Natural

Contact Features

Contact Size	.63mm
--------------	-------



Contact Type	Tab
Mating Tab Width	.64 mm[.025 in]

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	Yes
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT
Centerline (Pitch)	2.2 mm[.087 in]

Dimensions

Row-to-Row Spacing	4.4 mm[.173 in]
Product Width	18.6 mm[.732 in]
Product Length	33.9 mm[1.335 in]
Connector Height	14.7 mm[.579 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F]
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Other

Serviceable	Yes
Connector Position Assurance Capable	No



Product Compliance


For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 1743161-2
CLIP HSG FOR 025 CONN 12P



TE Part # CAT-T319-CH8172
TH/.025 CONNECTOR SYSTEM,
HOUSING



TE Part # 1674742-1
025 TH TAB CONTACT

Also in the Series | [TH/.025 Connector System](#)



Automotive Connector Locks & Position Assurance(1)



Automotive Headers(5)



Automotive Housings(60)




Automotive Terminals(4)



Insertion & Extraction Tools(4)



Other Automotive Connector Accessories(1)



PCB Headers & Receptacles(5)



Wire-to-Board Headers & Receptacles (5)

Customers Also Bought



TE Part #2109005-3
060 TAB(M) CONT



TE Part #2219192-2
025 16P SLD CAP ASSY



TE Part #2394139-1
025/060 HYB 4P PLUG




TE Part #2188204-2
025/060/110HYB 60P CAP ASSY



TE Part #2391056-2
12POS,TH 025,REC HSG,UNSLD,COD A



TE Part #2381535-2
TPA REC HSG,3POS,0.64 SERIES




TE Part #936240-1
090III 6P(S) CAP ASSY



TE Part #2381533-1
3POS,0.64 SERIES,REC HSG,COD A



TE Part #2343432-1
6POS,0.64 SERIES,REC HSG ASSY, COD A



TE Part #368260-2
CLIP HSG FOR 090 II MLC BLACK

Documents



Product Drawings

025 G 12POS CAP ASSY W TO W

Japanese

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1473407-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1473407-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1473407-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Crimping of 025 G Tab Contact

Japanese

Application Specification

Japanese

CRIMPING 025 TH TAB CONTACT

Japanese

Application Specification

Japanese

Instruction Sheets

025 G Wire to Wire Connector

Japanese

Instruction Sheet (non U.S.)

Japanese

025 G Wire to Wire Connector

Japanese

Instruction Sheet (non U.S.)

Japanese