

Buchanan | BUCHANAN 4 Series

TE Internal #: 1546927-4

4 Position Barrier Strip, Tri-Barrier, Printed Circuit Pin Bottom Termination, Wire-to-Board, 8.26 mm [.325 in] Centerline, 1 Row,

BUCHANAN 4 Series

View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips











Number of Positions: 4

Barrier Strip Style: Tri-Barrier

Bottom Termination Type: Printed Circuit Pin

Connector System: Wire-to-Board
Centerline (Pitch): 8.26 mm [.325 in]

Features

Product Type Features

Troduct Type realures	
Block Style	Flat Bottom with standoffs
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Levels	1
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Operating Voltage	300 V
Body Features	
Primary Product Color	Black
Product Orientation	Vertical
Barrier Strip Style	Tri-Barrier



Contact Features

Contact Base Material	Brass
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	15 A

Termination Features

Bottom Termination Type	Printed Circuit Pin	
-------------------------	---------------------	--

Mechanical Attachment

Top Termination Type	Wire Clamp Combo Head
Mounting Options	None
Screw Plating Material	Nickel
Screw Material	Steel
Thread Size	M3
Screw Head Type	Combo Phil-Slot
Connector Mounting Type	Board Mount

Housing Features

Housing Material	PBT
Centerline (Pitch)	8.26 mm[.325 in]

Dimensions

Product Length	34.21 mm[1.347 in]
Wire Size	22 – 14 AWG

Usage Conditions

Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]

Operation/Application

Industry Standards

UL Flammability Rating	UL 94V-0	
------------------------	----------	--

Packaging Features

Packaging Method	Package
Packaging Quantity	300

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series BUCHANAN 4 Series





Customers Also Bought



TE Part #1-1469492-8 MULTIGIG RT 9MM GUIDE/ESD 315 DEG



TE Part #1-1469492-9 MULTIGIG RT 9MM GUIDE/ESD UNKE



TE Part #1-1469492-7 MULTIGIG RT 9MM GUIDE/ESD 270 DEG



TE Part #1546927-2 2P .325 TRI-BARRIER W/COVER











MULTIGIG RT GUIDEPIN, 9MM 2.60





Documents

Product Drawings

4P .325 TRI-BARRIER W/COVER

English

CAD Files

Customer View Model

ENG_CVM_CVM_1546927-4_A.2d_dxf.zip

English

3D PDF

4 Position Barrier Strip, Tri-Barrier, Printed Circuit Pin Bottom Termination, Wire-to-Board, 8.26 mm [.325 in] Centerline, 1 Row, BUCHANAN 4 Series



3D

Customer View Model

ENG_CVM_CVM_1546927-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1546927-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS

English

1-1773458-2_BARRIER_STRIPS_QUICK_REFERENCE_GUIDE

English

Agency Approvals

UL

English