

MEAS | MEAS 154

TE Internal #: 154CV-005G-R

TE Internal Description: 5 PSIG RIBBON CABLE MV PRESSURE

SENSOR

19MM MV OUTPUT PRESSURE SENSOR

View on TE.com >



Sensors > Pressure Sensors > Media Isolated Pressure Sensors > 19MM MV OUTPUT PRESSURE SENSOR



Pressure Sensor Type: mV Output Pressure Sensors

Pressure Type: Gauge

Supply Voltage Range: 10 V

Operating Temperature Range: -40 - 125 °C [-40 - 257 °F]

Sensor Package: O-Ring Mount

All 19MM MV OUTPUT PRESSURE SENSOR (18)

Features

Product Type Features

Product Type Features	
Pressure Sensor Type	mV Output Pressure Sensors
Pressure Type	Gauge
Sensor Package	O-Ring Mount
Configuration Features	
Electrical Connection	Ribbon Cable
Electrical Characteristics	
Supply Voltage Range	10 V
Dimensions	
Product Diameter	18.97 mm[.746 in]
Product Height	13.8 mm[.54 in]
Usage Conditions	
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Other	

No Tube

Sensor Options



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6-trimethylphenyl)- (1% in Component part A) Tetraglyme (2% in Component part B) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





Also in the Series | MEAS 154





Customers Also Bought



TE Part #3-6318490-6 .5FHR04H,220,S,GIG,08/Sn,HT,NSYes



TE Part #2-320577-2 TERMINAL,PIDG R IR 10 3/8



TE Part #2-1625984-5 HSA50 1R2 5%






TE Part #170262-4
EIS CONNCTOR FORMING



TE Part #3-6318491-6 .5FHP08H,220,S,GIG,08/Sn,HT,NSYes



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_154CV-005G-R_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_154CV-005G-R_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_154CV-005G-R_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

154NCV

English

