TE Internal #: 160336-2

Closed Ring Tongue Terminal, 12 – 10 AWG, 5/16 / M8 Stud, 8.3

mm [.327 in] Stud Diameter, Open Barrel, Straight, Tin Plating,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 6530 – 10383 CMA

Stud Size: 5/16, M8

Features

Product Type Features

Shape Description	Circular/Oval
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	5/16, M8
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Body Features	
Product Weight	1.651 g
Contact Features	
Contact Base Material	Brass
Barrel Type	Open
Terminal Orientation	Straight
Terminal Plating Material	Tin

None

Contact Underplating Material



Mechanical Attachment

Wire Insulation Support	With
Dimensions	
	.15 in
Wire Size	6530 – 10383 CMA
Stud Diameter	8.3 mm[.327 in]
Tongue Thickness	.76 mm[.03 in]
Product Length	25.4 mm[1 in]
Barrel Inside Diameter	2.66 mm, 4.44 mm[.105 in][.175 in]
Compatible Insulation Diameter (Max)	5.31 mm[.209 in]
Compatible Insulation Diameter Range	3.8 – 5.3 mm[.15 – .209 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

TPBR

Compatible Parts












Customers Also Bought













TE Part #CAT-P87074-C1701 Standard Temperature Caps | POWER TRIPLE LOCK









Documents

Product Drawings

RING TONGUE IS 12-10 0.295 X .650 TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160336-2_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160336-2_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160336-2_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Specification

English

Product Specification

English