



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **254 – 642 CMA**

Mating Tab Width: **2.8 mm [.11 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.79 mm[.031 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------



Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	14 mm[.55 in]
Compatible Insulation Diameter Range	1.01 – 2.03 mm[.04 – .08 in]
Terminal Material Thickness	.25 mm[.01 in]
Wire Size	254 – 642 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Reel

Other

Line	Premier
------	---------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150467-2
OCEAN_2.0_Applicator-E-055F090F-REA

KIT
REPRESENTATION ONLY

TE Part # 7-2150467-7
OCEAN_2.0_SPARE_PART_KIT-055F090F

TE Part # 2150467-1
OCEAN_2.0_Applicator-E-055F090F-REM

Also in the Series | FASTON 110

Crimp Terminal Housings(13)

Insertion & Extraction Tools(1)

PCB Terminals(22)

Quick Disconnects(164)

Customers Also Bought

TE Part #2837157-1
OCEAN_2.0_Applicator-S-110F1550-RSM

TE Part #925387-1
110 FASTON HSG. REC. 1P CLEAR

TE Part #5-929008-2
MQS1MM BU-KONT 90GR

TE Part #163087-9
062 SOC.ASS. TYP3+





CRIMPER REPRESENTATION ONLY

TE Part #7-2119582-6
CRIMPER, INSULATION F PREMIUM



ANVIL REPRESENTATION ONLY

TE Part #1803426-2
ANVIL, COMBINATION, NO JOG, END FEED



TE Part #60573-1
187 FASTON REC 24-20 TPBR



TE Part #6-353908-2
CT REC HSG 2P CRIMP TYPE BLUE



TE Part #4-2407269-3
CAP, CPC, SIZE 17 RECP, RED



TE Part #2141501-1
3POS, 1.5MM SFC, REC HSG, ASSY, SEALED, BK

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160772-3_C_c-160772-3-c.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160772-3_C_c-160772-3-c.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160772-3_C_c-160772-3-c.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL

English