



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.03 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

	.057 in
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	19.2 mm[.755 in]
Compatible Insulation Diameter Range	1.4 – 2.3 mm[.055 – .09 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	.51 – 1.03 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	5000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 160871-6
FF 250 REC TERMINAL FLAG 20-17
TPBR

TE Part # 626094-1
TERMINAL, .250 FASTIN-ON REC

TE Part # 626094-2
FF .250 REC 0.5 /1.0 MM2 0.32X19.3
TPBR

TE Part # 7-2150193-7
OCEAN_2.0_SPARE_PART_KIT-
080F110OV

TE Part # 2150193-2
OCEAN_2.0_Applicator-E-080F110OV-
REA

TE Part # 2150193-1
OCEAN_2.0_Applicator-E-080F110OV-
REM

TE Part # 63467-1
FF 250 REC 14-10AWG TPBR

TE Part # 626328-2
FF 250 RECEPTACLE 4.0-6.0 MM2
TPBR

TE Part # 1-1579007-4
EXTRACTION TOOL

TE Part # 4-1579007-3
EXTRACTION TOOL KIT

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(195)

Insertion & Extraction Tools(2)

Quick Disconnects(216)

Customers Also Bought



TE Part #7611793001
VG-95218-T025-G010



TE Part #3870123006
44A1111-18-9-9



TE Part #180384-2
FF 250 REC 4-6MM2 PTBR LP



TE Part #EM1371-000
CBS-24C621-43M-9



TE Part #K1143488
Limit switch G12-231-S-10 910



TE Part #160655-2
FASTON 110 REC 20-15 AWG PTPB



TE Part #880810-1
COVER CAP , 2 WAY



TE Part #6176350001
TMS-SCE-3/4-2.0-S1-4



TE Part #K1007174
Toggle Switch 08-1-1-12 F



TE Part #8B-0067-001-000
617/917 METAL PROTECTION CAP
FOR PLUG

Documents

Product Drawings

6,35 FASTIN-FASTON RECEP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160860-3_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160860-3_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160860-3_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English