

HF4A1201D00 ✓ ACTIVE

CII

TE Internal #: 1617036-6

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2
Form C DPDT-CO, 4 A Contact Rating, 26.5 – 32 VDC Coil Voltage, .
684 W Coil Power

[View on TE.com >](#)

Relays & Contactors > Electromechanical Relays

Relay & Contactor Type: **General Purpose Signal Relay**

Current Type: **DC**

Coil Magnetic System: **Non-Polarized, Monostable**

Contact Arrangement: **2 Form C DPDT-CO**

Contact Current Rating: 4 A

Features

Product Type Features

Relay & Contactor Type	General Purpose Signal Relay
------------------------	------------------------------

Configuration Features

Contact Arrangement

2 Form C DPDT-CO

Electrical Characteristics

Coil Resistance	1250 Ω
Contact Current Rating	4 A
Coil Voltage Rating	26.5 – 32 VDC
Coil Power Rating DC	.684 W

Body Features

Enclosure Type	Hermetically Sealed
----------------	---------------------

Termination Features

Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins

Mechanical Attachment

Product Mount Type	Board Mount
--------------------	-------------

Usage Conditions

Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
-----------------------------	----------------------------



Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Vibration Resistance	20G's, 10 – 2000Hz
Shock Resistance	100G's, 6ms
Current Type	DC
Coil Magnetic System	Non-Polarized, Monostable

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (40% in Component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1617125-2
JMAW-6XL = M39016/9-014L



TE Part # 6-1617596-2
MGSCDG-6W=RELAY



TE Part # 1617353-6
JMSWT-26XM=M28776/3-022M



TE Part # 3-1617599-3
PRMGACDG-12X=RELAY



TE Part # 5-1617592-4
JMSCT-9XM=M28776/3-035M



TE Part # 7-1617542-0
JMGACD-18M=M39016/18-035M



TE Part # 6-1617573-0
JMGSCG-48LW=M39016/41-070L



TE Part # 8-1617540-5
J1MAWT-26XL=M28776/5-018L



TE Part # 5-1617590-4
J1MACT-12XLS=M28776/5-034L



TE Part # 5-1617591-4
J1MSWT-12XP=M28776/4-020P



TE Part # 4-1617571-9
JMGACG-6PW=M39016/17-050P



TE Part # 5-1617540-5
J1MACD-5XMS=M39016/23-031M



TE Part # 6-1617564-9
J1MAPDD-26XM=M39016/24-024M



TE Part # 9-1617542-4
JMGSC-12P=M39016/41-035P



TE Part # 7-1617571-0
JMGAPDD-9L=M39016/19-027L



TE Part # 5-1617564-4
J1MACDD-9XP=M39016/24-027P



TE Part # 2-1617573-8
JMGSCDG-6LW=M39016/42-066L



TE Part # 1-1617572-2
JMGSCD-9LW=M39016/42-055L



TE Part # 5-1617566-9
J1MSWDD-40XM=M39016/26-022M



TE Part # 3-1617591-8
J1MSPT-26XP=M28776/4-030P

Customers Also Bought



TE Part #5745968-8
HD-20 25 PLUG SP/FMS INSRT



TE Part #2176439-2
CRGH 0603 1% 10R-1M0 LAB-KIT




TE Part #2176439-1
CRGH 0402 1% 10R-1M0 LAB-KIT




TE Part #5747871-8
09 PLUG SP/FMS INSRT



TE Part #4-1437621-2
KB700B1/4=KNOB KNURL BLACK 1/4



TE Part #823696-000
382A023-25-0



TE Part #CAT-R21-731072
Bulbous Heat Shrink Boots: Lipped,
Straight



TE Part #7035563001
44A0111-22-9CK0001

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1617036-6_7.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1617036-6_7.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1617036-6_7.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

5-1773450-5_sec1_HFW4A

English

RELAY

English