3SBH1146A2 <

CII

TE Internal #: 1617348-4 General Purpose Signal Relay, DC, Non-Polarized, Monostable, 4 Form C 4PDT-CO, 2 A Contact Rating, 12 VDC Coil Voltage, 1.252 W Coil Power

View on TE.com >

Relays & Contactors > Electromechanical Relays > 4PDT Signal Relay: Electrically-Held, 1/5-Size Relay



Relay & Contactor Type: General Purpose Signal Relay

Current Type: DC

Coil Magnetic System: Non-Polarized, Monostable

Contact Arrangement: 4 Form C 4PDT-CO

Contact Current Rating: 2A

All 4PDT Signal Relay: Electrically-Held, 1/5-Size Relay (24)

Features

Product Type Features

Relay & Contactor Type

General Purpose Signal Relay



Configuration Features

Contact Arrangement	4 Form C 4PDT-CO				
Electrical Characteristics					
Coil Resistance	115 Ω				
Contact Current Rating	2 A				
Coil Voltage Rating	12 VDC				
Coil Power Rating DC	1.252 W				
Body Features					
Enclosure Type	Hermetically Sealed				
Termination Features					
Main Termination & Connection Type	Solder Hook Terminals				
Coil Termination & Connection Type	Solder Hook Terminals				
Mechanical Attachment					
Product Mount Type	Chassis Mount				

3SBH1146A2

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 4 Form C 4PDT-CO, 2 A Contact Rating, 12 VDC Coil Voltage, 1.252 W Coil Power



Usage Conditions

Operating Temperature Range	-65 – 125 °C				
Environmental Ambient Temperature (Max)	125 °C[257 °F]				
Operation/Application					
Vibration Resistance	30G's, 10 – 3000Hz				
Shock Resistance	75G's, 6ms				
Current Type	DC				
Coil Magnetic System	Non-Polarized, Monostable				

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant	
EU ELV Directive 2000/53/EC	Not Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC	

Solder Process Capability

Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

3SBH1146A2

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 4 Form C 4PDT-CO, 2 A Contact Rating, 12 VDC Coil Voltage, 1.252 W Coil Power





Customers Also Bought



JIVIAC - 18XP = IVI39016/9-061P	WIVIATE, RCPT, 62P, PSTD LF	HF3 / 2 = 500 HIVI / 01010V 4.5V BIST	30 SYSTEM 50 HDR DRST SHRD
		1COIL	

NANAATE DODT (20



IN A C 101/D NA2001 / /0 0/1D

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1617348-4_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1617348-4_D.3d_igs.zip

English

3SBH1146A2

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 4 Form C 4PDT-CO, 2 A Contact Rating, 12 VDC Coil Voltage, 1.252 W Coil Power



Customer View Model

ENG_CVM_CVM_1617348-4_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773450-5_sec1_3SBH

English