166995-2 - ACTIVE

AMPLIMITE

TE Internal #: 166995-2 Pin Contact, Gold (Au), Snap-In Contact Retention, Size 20 Contact Size, 32 – 28 AWG, .032 – .09 mm² Wire, Crimp, Brass, Signal View on TE.com >



Connectors > Contacts > Connector Contacts > D-Sub Connector Contacts: Pin, Brass, Signal, Size 20



Contact Type: Pin

Contact Mating Area Plating Material: Gold (Au)

Contact Retention Type Within Housing: Snap-In

Contact Size: Size 20

Wire Size: 32 – 28 AWG

All D-Sub Connector Contacts: Pin, Brass, Signal, Size 20 (45)

Features

Contact Features

Contact Underplating Material	Nickel
Mating Pin Diameter	1 mm
PCB Contact Termination Area Plating Material	Gold Flash
Contact Mating Area Plating Material Thickness	.8 μm
Contact Type	Pin
Contact Mating Area Plating Material	Gold (Au)
Contact Size	Size 20
Contact Base Material	Brass
Contact Current Rating (Max)	1.2 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable
Mechanical Attachment	

C For support call+1 800 522 6752

166995-2

Pin Contact, Gold (Au), Snap-In Contact Retention, Size 20 Contact Size, 32 – 28 AWG, .032 – .09 mm² Wire, Crimp, Brass, Signal



Wire Insulation Support	With	
Contact Retention Type Within Housing	Snap-In	
Dimensions		
Compatible Insulation Diameter Range	.5 – 1.02 mm[.02 – .04 in]	
Wire Size	.032 – .09 mm²	
Usage Conditions		
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]	
Operation/Application		
Circuit Application	Signal	
Identification Marking		
Contact Color Code	Black	
Packaging Features		
Packaging Method	Reel	
Packaging Quantity	12500	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

166995-2

Pin Contact, Gold (Au), Snap-In Contact Retention, Size 20 Contact Size, 32 – 28 AWG, .032 – .09 mm² Wire, Crimp, Brass, Signal



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # 2837676-2 OCEAN-2.0-APPLICATOR-S-033F050O-SSA



Customers Also Bought



	TE	The the the the	
TE Part #1658671-1	TE Part #205206-3	TE Part #66102-7	TE Part #1-106505-2
HDP-22,PLUG,SIZE 2, 26 POSN	CRIMP SNAP PLUG ASSY,SIZE 2	III+ PIN,24-20,TIN-LEAD,STRIP	9P.HDP20 REC.ASSY.



TE Part #794192-1 08P MINI UMNL2 PLUG HSG UL94V0

Documents

Product Drawings 20DP CRIMP PIN

English

C For support call+1 800 522 6752

166995-2

Pin Contact, Gold (Au), Snap-In Contact Retention, Size 20 Contact Size, 32 – 28 AWG, .032 – .09 mm² Wire, Crimp, Brass, Signal



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_166995-2_V.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_166995-2_V.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_166995-2_V.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English