




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	.93 mm
Wire Insulation Support	With
Mating Retention Type	Locking Lance
Extraction Force	4.9 – 34.3 Newton

Dimensions

Product Length	21.5 mm[.846 in]
Compatible Insulation Diameter Range	2.2 – 3.4 mm[.086 – .134 in]
Terminal Material Thickness	.33 mm[.013 in]
Wire Size	.51 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2819183-1
.250 SERIES FASTIN FASTON REC.

TE Part # 2150034-2
OCEAN_2.0_APPLICATOR-E-110F180FA-REA

TE Part # 7-2150034-7
OCEAN_2.0_SPARE_PART_KIT-110F180F

TE Part # 170303-1
FF 250 REC 22-18AWG BR WITH LATCH

TE Part # 2150034-1
OCEAN_2.0_APPLICATOR-E-110F180F-REM

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(195)

Insertion & Extraction Tools(2)

Quick Disconnects(216)

Customers Also Bought



TE Part #2066499-1
12 POS DBL PLATE FOR CAP

TE Part #2066043-1
12 POS. ECONOSEAL CAP HOUSING JMARK II+

TE Part #2066042-1
12 POS.ECONOSEAL PLUG HSG ASSY JMARK II+

TE Part #170030-2
FF 250 TAB 20-14AWG TPBR

TE Part #1801174-4
2W TAB HP CONNECTOR YELLOW

TE Part #2066046-3
2 POS MINI FUSE BOX ASSY

TE Part #2312552-1
COVER,44P DIRECT CONNECTOR

TE Part #316390-7
CAVITY PLUG FOR MINI M/LOCK

TE Part #2066500-1
12 POS ECONOSEAL DBL PLATE PLUG

TE Part #2066043-2
12 POS. ECONOSEAL CAP HOUSING JMARK II+

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170031-2_AF_c-170031-2-af.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170031-2_AF_c-170031-2-af.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170031-2_AF_c-170031-2-af.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Crimping of 250 Series Tab and Receptacle Contacts

Japanese

Application Specification

Japanese



Application Specification

Japanese

Crimping of 250 Series Tab and Receptacle Contacts

Japanese

Agency Approvals

UL Report

English