




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.31 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	.79 mm
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	20.5 mm[.807 in]
Compatible Insulation Diameter Range	2.16 – 3.43 mm[.085 – .135 in]
Terminal Material Thickness	.33 mm[.013 in]
Wire Size	.51 – 1.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 934678-1
DAHT 250 REC 20-14 ASSY

TE Part # 968864-2
2 POS. FASTON HOUSING

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(195)

Insertion & Extraction Tools(2)

Quick Disconnects(216)

Customers Also Bought

TE Part #174355-7
070 ECONOSEAL MARK-2 P/CAP 2P

TE Part #172130-1
FF 250 REC HSG 2P NYLON NAT


TE Part #173706-1
E-J MK-2 070 TAB CONT LP

TE Part #2822354-1
070 TYPE RUBBER PLUG





TE Part #DT06-3S-PP01
PLG, 3P, BLK, SEAL RET, 120 OHM
RESISTOR




TE Part #180941
FF 250 REC HSG 3P NYLON NAT



TE Part #CAT-EC7491-CH8172
ECONOSEAL, CONNECTOR
HOUSING



TE Part #175287-2
DYNAMIC D-3 TAB CONT. S AU 0.38 L
/P



TE Part #174360-7
070 ECONOSEAL MARK-2 P/CAP 3P

Documents

Product Drawings

FF 250 REC 20-14AWG BR LP

Japanese

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170054-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170054-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170054-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Crimping of 250 Series Tab and Receptacle Contacts

Japanese

Application Specification

Japanese

Application Specification

Japanese

Crimping of 250 Series Tab and Receptacle Contacts

Japanese



[Agency Approvals](#)

[UL Report](#)

English