Positive Lock | Positive Lock 312

TE Internal #: 170381-1

Quick Disconnect Receptacle, 20 – 14 AWG, .51 – 2.08 mm² Wire, 7.92 mm [.312 in] Tab Width, Straight, Brass, Tin Plating, Positive

Lock 312

View on TE.com >



Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: .51 – 2.08 mm²

Mating Tab Width: 7.92 mm [.312 in]

Mating Tab Thickness: .76 mm [.03 in]

Features

Product Type Features

Insertion Force

	1 (0111101
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single
Contact Features	
Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	7.92 mm[.312 in]
Mating Tab Thickness	.76 mm[.03 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Normal



Product Terminates To	Wire & Cable
Mechanical Attachment	
Wire Insulation Support	With
Mating Retention Type	Dimple
Extraction Force	.7 – 10.2 kgf
Dimensions	
Product Length	22.5 mm[.886 in]
Compatible Insulation Diameter Range	2.21 – 3.4 mm[.087 – .134 in]
Terminal Material Thickness	.33 mm[.013 in]
Wire Size	.51 – 2.08 mm²
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Industry Standards	
Compatible With Agency/Standards Products	UL
Packaging Features	
Packaging Quantity	15000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability
Product Compliance Disclaimer	

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









OCEAN_2.0_Applicator-E-090F130F-REA

Also in the Series | Positive Lock 312







Insertion & Extraction Tools(1)



Quick Disconnects(5)

Customers Also Bought























Documents

Product Drawings

PL .312 REC AV 0.5-2 MM2 PRE-TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170381-1_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170381-1_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170381-1_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English