

FASTIN-FASTON | FASTIN-FASTON 375

TE Internal #: 171447-2

Receptacle, Receptacle, 2 Position, Straight, Black, Nylon, Cable Mount (Free-Hanging), FASTIN-FASTON 375, Crimp Terminal

Housings

View on TE.com >



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings











Terminal Type: Receptacle

Connector & Housing Type: Receptacle

Number of Positions: 2

Terminal Orientation: Straight
Primary Product Color: Black

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector & Housing Type	Receptacle
Configuration Features	
Number of Positions	2
Body Features	
Primary Product Color	Black

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

Mechanical Attachment

Mating Retention Type	Mating Retention Type	Latch
-----------------------	-----------------------	-------



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Nylon
Centerline (Pitch)	12.3 mm[.484 in]
Dimensions	
Product Length	33 mm[1.3 in]
Usage Conditions	
Operating Temperature Range	-40 – 150 °C[-40 – 302 °F]
Packaging Features	
Packaging Quantity	500

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



FF 375 REC 6-10MM2 TPBR



Also in the Series | FASTIN-FASTON 375







Insertion & Extraction Tools(1)



Quick Disconnects(16)

Customers Also Bought




TE Part #6368077-2 2X4 OFFSET STK MJ,SHLD,RJ45,W /GND



TE Part #5-794680-0 20P MICRO MNL ASSY,VRT,THRU LF



TE Part #2227581-1 1X2 R/A ASSY, MINI SAS HD INTERNAL



TE Part #5-104894-6 60 50/50 GRID RA HDR LF



TE Part #102203-1 04 MODII HDR SRRA SHRD .100CL



TE Part #1-440054-4
2.0MM,HDR,14POS,VERTICAL



TE Part #1-1563878-1 15POS, MIXED,REC HSG,SEALED,AS



TE Part #1-5745968-3 25 PLUG SP/FMS SCRLK







Documents

Product Drawings

FF 375 PLUG HSG 2P NYLON BLACK

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_171447-2_D_c-171447-2-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_171447-2_D_c-171447-2-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_171447-2_D_c-171447-2-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English