



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-2**

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without

Mechanical Attachment

Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)



Housing Features

Housing Material	Nylon
------------------	-------

Dimensions

Product Length	24.4 mm[.961 in]
Wire Size	14 AWG

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Quantity	2000
--------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts

 TE Part # 63609-1 250 FASTON REC 22-18 AWG BR	 TE Part # 737440-2 250 FASTON REC 17-14 AWG TPBR	 TE Part # 42640-2 250 FASTON REC 22-18 AWG TPBR	 TE Part # 41450-1 250 FASTON REC 14-10 AWG TPBR
--	--	--	--


Also in the Series | FASTON 250

 Compression Connectors(4)	 Crimp Terminal Housings(116)	 Insulation Boots & Sleeves(16)	 Magnet Wire Terminals(1)
 PCB Terminals(134)	 Quick Disconnects(421)	 Splices(4)	

Customers Also Bought

 TE Part #1-172469-1 PL 250 HOUSING NATURAL 6/6 NYLON	 TE Part #1744544-7 EP II TPA 07P, BLACK	 TE Part #917705-1 2.5 SIGNAL DBL LOCK D.L.P. 9P	 TE Part #917684-1 2.5 SIGNAL DBL LOCK REC CONT M
---	---	--	---





TE Part #63609-1
250 FASTON REC 22-18 AWG BR



TE Part #62811-2
250 FASTON FLAG REC 18-14 AWG TPBR



TE Part #917765-1
2.5 SIGNAL D/LOCK TAB CONT. M



TE Part #1-1744416-1
11 POS EP II HSG, GLOW WIRE



TE Part #CAT-SI261-P729
STD Temp Signal Double Lock Plug

Documents

Product Drawings

FASTON 250 INS POD NYLON NAT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_171706-1_L1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_171706-1_L1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_171706-1_L1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

FASTON Housings

English

Product Specifications

AMPIP POD

Japanese

Product Specification

Japanese



Agency Approvals

UL Report

English

UL Report

English