



Connectors > Audio & Video Connectors > USB Connectors



USB Adapter Type: **A**

USB Version: **2.0**

Connector Profile: **Standard**

Connector & Housing Type: **Receptacle**

Number of Ports: **1**

Features

Product Type Features

USB Adapter Type	A
USB Version	2.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
USB Connector Type	USB 2.0 Type-A

Configuration Features

Number of Mounting Legs	2
Number of Ports	1
Number of Positions	4

Body Features

Shell Plating Finish	Bright
Shell Plating Material	Tin
Connector Profile	Standard



Contact Features

Contact Mating Area Plating Material Thickness	.76 µm[29.92 µin]
Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
Contact Current Rating (Max)	1 A

Termination Features

Termination Post & Tail Length	2.8 mm[.11 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Locking Feature	Without
PCB Mount Location	Top
PCB Connector Seating	Flush
PCB Mount Retention Type	Kinked Legs
Panel Mount Feature Type	Flange
Connector Mounting Type	Board Mount

Housing Features

Housing Material	Thermoplastic
Housing Color	Black
Body Orientation	Vertical
Centerline (Pitch)	2 mm, 2.5 mm[.078 in][.098 in]

Dimensions

PCB Thickness (Recommended)	1.6 mm[.063 in]
-----------------------------	-----------------

Usage Conditions

Soldering Temperature (Max)	240 °C[464 °F]
Mating Cycles (Max)	1500
Operating Temperature Range	-40 – 80 °C[-40 – 176 °F]

Operation/Application

Halogen Free	No
Circuit Application	Power & Signal

Industry Standards

Industry Standard	USB 2.0
Moisture Sensitivity Level	1
Test Identification (TID)	60000042



UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity	120
Packaging Method	Box & Tray, Tray

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2142872-1
cable assy, usb a plug to 5p hsg




TE Part # 1487595-3
USB, A-B, 28/26, BLACK, .83M



TE Part # 1827525-1
MECHATROLINK II CONNECTOR KIT




TE Part # 1929690-1
USB CABLE, USB A to Mini USB,Blue



TE Part # 1487595-2
USB, A-B, 28/26, BLACK, 1.3M



TE Part # 1-1734028-3
Std USB, Type A, Plug



TE Part # 1487594-3
USB, A-B, 28/28, BLACK, 0.16M



TE Part # 1487593-2
USB, A-BLUNT,28/24,WHT,1.5M



TE Part # 1496476-1
STD USB-A TO MINI-B ASSY, 1M



TE Part # 1487593-1
USB, A-BLUNT,28/24,WHT,2.0M



TE Part # 1-1734028-1
Std USB, Type A, Plug, Natural



TE Part # 1487600-1
USB, A-BLUNT,28/26,BLK,1.0M



TE Part # 1734028-1
Std USB Type A, Plug, Natural



TE Part # 1487594-2
USB, A-B, 28/28, BLACK, 0.25M



TE Part # 1487595-1
USB, A-B, 28/26, BLACK, 1.0M




TE Part # 1487594-1
USB, A-B, 28/28, BLACK, 0.5M



TE Part # 1487599-1
USB, A-BLUNT,28/28,BLK,0.83M

Customers Also Bought




TE Part #6-794636-6
06P MICRO MNL ASSY,VRT,SMT,LF



TE Part #1-641972-1
09P UMNL PIN HDR ASSY BLACK



TE Part #2387135-1
PLUG CONN CA, REV, SER 2,SZ 17-28, L 0.5M




TE Part #281699-4
HEADER HE13 RA 4 P







TE Part #641991-5
07P MTA156 HDT SQ W/O#1,4,6



TE Part #1SNG620025R0000
EP-ROP-M25-LGR-C



TE Part #284944-E
STVC/2 48 F ABC VV 7-00 TL 4,0 * 247 E0



TE Part #354108-E
STVM 42-6 F ABC VV 7-00 TL 4,0 * 247 E0



TE Part #5-1437581-6
ASF22=DPDT AUTO-SLIDE

TE Part #2205519-1
CA MICRO-MATCH MOW-MOW 8POS

Documents

Product Drawings

Std USB Type A, VT, T/H

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1734366-1_C1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1734366-1_C1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1734366-1_C1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

USB Quick Reference Guide (English)

English

USB and Mini USB Datasheet 7-1773442-0

English

Product Specifications

Product Specification

English



Product Specification

English

Agency Approvals

UL Report

English