TE Internal #: 1735078-1

SAS, Plug, Wire-to-Board, 29 Position, 1 Row, 1 Port, Right Angle, Surface Mount, Power & Signal, Board Mount, -40 – 85 °C [-40 – 185

°F1

View on TE.com >



Connectors > PCB Connectors > SAS & MiniSAS > Serial Attached SCSI (SAS) Connector Plugs











SAS Connector Type: SAS

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 29

Number of Rows: 1

All Serial Attached SCSI (SAS) Connector Plugs (3)

### Features

### **Product Type Features**

Connector & Contact Terminates To	Printed Circuit Board
Shell	Without
SAS Connector Type	SAS
Connector & Housing Type	Plug
Connector System	Wire-to-Board

### **Configuration Features**

Number of Positions	29
Number of Rows	1
Number of Ports	1
PCB Mount Orientation	Right Angle

### **Body Features**

|--|

#### **Contact Features**



Contact Underplating Material	Nickel			
Contact Mating Area Plating Material	Gold (Au)			
Contact Base Material	Copper Alloy			
PCB Contact Termination Area Plating Material	Tin			
	30 μin			
Contact Current Rating (Max)	1.5 A			
Termination Features				
Termination Method to PCB	Surface Mount			
Mechanical Attachment				
PCB Mount Retention	Without			
Connector Mounting Type	Board Mount			
Housing Features				
Housing Material	Thermoplastic			
Usage Conditions				
High Temperature Housing	Yes			
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]			
Operation/Application				
Circuit Application	Power & Signal			
Industry Standards				
UL Flammability Rating	UL 94V-0			
PCIe/SAS Generation	Gen2			
Packaging Features				
Packaging Method	Loose Piece			

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candida	ate Li	st De	eclared	Against:	JAN	2025
(247)						
				1 () // 1 (		

Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability Pin-in-Paste capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



# Customers Also Bought























### **Documents**

### **Product Drawings**

SAS PLUG 15+7+7P ASSEMBLY

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1735078-1\_C2.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1735078-1\_C2.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1735078-1\_C2.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

**Product Specification** 

English