




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **5.21 mm [.205 in]**

Terminal Orientation: **Straight**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	5.21 mm[.205 in]
Terminal Orientation	Straight
Contact Base Material	Steel
Terminal Plating Material	Nickel
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------



Dimensions

Compatible Insulation Diameter Range	2.54 – 3.81 mm[.1 – .15 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]

Packaging Features

Packaging Quantity	16000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts






KIT

REPRESENTATION ONLY

TE Part # 7-2150084-7

OCEAN_2.0_SPARE_PART_KIT-100F180F



TE

TE Part # 2150084-1

OCEAN_2.0_APPLICATOR-E-100F180F-REM




TE

TE Part # 2150084-2

OCEAN_2.0_APPLICATOR-E-100F180F-REA

Also in the Series | FASTON 205



Crimp Terminal Housings(3)



PCB Terminals(10)



Quick Disconnects(35)

Customers Also Bought



TE

TE Part #1742899-1

187 FASTON,REC.,18-16 OR 2X18 AWG,NPST



TE

TE Part #63696-1

187 FASTON REC 20-16 AWG NPST



TE

TE Part #63933-2

250 PL MKIII REC. 22-18AWG TPBR



TE

TE Part #63674-1

250 FASTON REC 18-14 AWG NPST



TE

TE Part #1742543-1

250 FASTON,FLAG,REC.,18-12 AWG, NPST



TE

TE Part #63963-1

250 FASTON FLAG REC 18-14 AWG NPST



TE

TE Part #1969443-8


EP 2.5 TPA Retainer, 8 Pos



TE

TE Part #350865-1


01P UMNL PLUG HSG



TE

TE Part #63539-1

250 FASTON REC 14-10 AWG TPBR



TE

TE Part #1-176282-5

AMP UNIVERSAL POWER CAP 2P GREEN



Documents

Product Drawings

205 FASTON,REC.,18-14 AWG,NPST

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1742594-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1742594-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1742594-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English