



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **500 – 1900 CMA**

Mating Tab Width: **6.35 mm [.25 in]**

Features

Product Type Features

Compatible With Discrete Wire Type	Magnet Wire
Insertion Force	High

Configuration Features

Connection Capacity	Single
---------------------	--------

Electrical Characteristics

Voltage Rating	240 V
----------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open



Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	13.46 mm[.53 in]
Compatible Insulation Diameter Range	2.54 – 3.05 mm[.1 – .12 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	500 – 1900 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Packaging Features

Packaging Quantity	15000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits





as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





 TE Part # 63944-1 RCPT 250 FLG FAST AMVAR TPPHBZ	 KIT TE Part # 7-2150450-7 OCEAN_2.0_SPARE_PART_KIT-070F140OV	 TE Part # 1217624-1 .187 FAST FL AMVR 0157 TPBR	 TE Part # 63480-1 RCPT STATOR 27-22 0173PTPBR
 TE Part # 1742678-2 187 RCPT FAST AMVR 0157TPPB	 TE Part # 2150450-2 OCEAN_2.0_Applicator-E-070F140OVA-SEA	 TE Part # 1599721-1 TAB REC, STATOR, AMPLIVAR	 TE Part # 1217955-1 .187 FAST FL AMVAR 0157 TPBR
 TE Part # 63942-1 RCPT,187 FL/FAST/AMVR 0157TPBR	 TE Part # 63940-1 RCPT.187 FL/FAST AMVR 0157TPB	 TE Part # 505081-1 AMPLIVAR .248 DUAL BLADE PTPBR	 TE Part # 63941-1 RCPT 187 FL/FAST AMVR 0157TPBR
 TE Part # 1217417-1 RCPT.187 FL/FAST AMVR .157TPB	 TE Part # 2150450-1 OCEAN_2.0_Applicator-E-070F140OV-SEM	 TE Part # 1-969049-1 AMPLIVAR STATOR BUCHS	 TE Part # 63964-1 REC STATOR 2800/7400 PTPBR




Also in the Series | **AMPLIVAR**



Customers Also Bought





Documents

Product Drawings

250 FAST FLG RCPT AMVAR TPBR

English

250 FAST FLG RCPT AMVAR TPBR

English

250 FAST FLG RCPT AMVAR TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1742881-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1742881-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1742881-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English