




Positive Lock | Positive Lock 250

TE Internal #: 175022-1

Quick Disconnect Receptacle, 18 – 14 AWG, .82 – 2.08 mm² Wire,
6.35 mm [.25 in] Tab Width, Straight, Brass, Pre-Tin Plating, Positive
Lock 250

[View on TE.com >](#)

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Electrical Characteristics

Voltage Rating	250 V
----------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Product Length	21.2 mm[.834 in]
Compatible Insulation Diameter Range	2.2 – 3.4 mm[.086 – .133 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	4500
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability







Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 6-1611018-9 ACC438UMM20=40A 3P 120V MODEL	 TE Part # 2376591-1 250 FASTON PCB TAB TPBR	 TE Part # 2-1393250-2 W28-XQ1A-0.75=W28	 TE Part # 6-1393114-8 KUHP-11A51-12=KU
 TE Part # 3-1393250-4 W28-XQ1A-3=W28-	 TE Part # 2150057-2 OCEAN_2.0_APPLICATOR-E-110F180F-REA	 TE Part # 1-1423673-0 W51-A122B1-7=CKTBKR,THERM, ROCK	 TE Part # 1-1423673-6 W51-A151A1-7=CKTBKR,THERM, ROCK
 TE Part # 1-1393253-4 W68-X2Q10-10=M6/M7/M9/W6/W7	 TE Part # 1-1423673-4 W51-A122B1-20=CKTBKR,THERM,ROC	 KIT REPRESENTATION ONLY TE Part # 7-2150057-7 OCEAN_2.0_SPARE_PART_KIT-110F180F	 TE Part # 1423675-6 W57-XB7A4A10-8=CKTBKR,THERM,PB
 TE Part # 1423673-1 W51-A121B1-5=CKTBKR,THERM, ROCK	 TE Part # 1423673-4 W51-A121B1-8=CKTBKR,THERM, ROCK	 TE Part # 1423673-6 W51-A121B1-15=CKTBKR,THERM,ROC	 TE Part # 1423000-7 W54-FA2A6A10-5



TE Part # 1-1423673-7
W51-A151A1-10=CKTBKR,THERM, ROC



TE Part # 1-1423364-2
W57-XB1A4A10-5=CKTBKR,THERM, PB,QC.250,BU



TE Part # 2-1393250-6
W28-XQ1A-11=W28



TE Part # 2-1393253-4
W68-X2Q110-30=M6/M7/M9/W6/W7

Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(177)



Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(5)



Quick Disconnects(173)

Customers Also Bought



TE Part #1-282002-5
AMP MONO-SHAPE TAB CONN



TE Part #1-284396-1
AMP MONO-SHAPE 3 POS TAB CONN




TE Part #1-368587-1
PDL 4P CAP 3.96 D/R F/H(GWT) N



TE Part #1746973-1
GRACE INERTIA CONNECTOR 6.2 MM PITCH TAB



TE Part #3-2005820-9
CLUSTER BLOCK 3P SLIM HSG(GWT)



TE Part #173724-1
187 PL EX REC. 20-14AWG PTBR



TE Part #1SNG601185R0000
EP-SG-PG7-GR-B



TE Part #1-282002-2
AMP MONO-SHAPE TAB CONN 2P. G



Documents

Product Drawings

250 PL EX REC. 18-14AWG PTBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_175022-1_L_c-175022-1-l.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_175022-1_L_c-175022-1-l.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_175022-1_L_c-175022-1-l.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

POSITIVE LOCK EX CONTACT

English

Agency Approvals

Agency Approval Document

English