1776113-8 ACTIVE

Buchanan

TE Internal #: 1776113-8

8 Position PCB Terminal Block, Header, Wire-to-Board, 3.81 mm [. 15 in] Centerline, 1 Row, 90° Wire Entry Angle, 28 – 16 AWG, .08 –

1.4 mm² Wire

View on TE.com >





Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Number of Positions: 8

Terminal Block Connector Type: Header

Connector System: Wire-to-Board
Centerline (Pitch): 3.81 mm [.15 in]

Number of Rows: 1

Features

Product Type Features

Wire Protection	With
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stacking Configuration	Side Stackable
Stacked Levels	Without
Number of Positions	8
Number of Rows	1
Wire Entry Angle	90°
Wire Entry Location	Side
Electrical Characteristics	
Operating Voltage	150 VAC



Driman, Draduct Calar	Dlagk
Primary Product Color	Black
Product Orientation	Vertical
Contact Features	
Contact Mating Area Plating Material	Tin (Sn)
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	12 A
Termination Features	
Termination Post & Tail Length	2.6 mm[.102 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Screw Plating Material	Nickel
Screw Material	Copper Alloy
Thread Size	M2
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	High Temperature Polyamide
Centerline (Pitch)	3.81 mm[.15 in]
Dimensions	
Wire Size	28 – 16 AWG
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Quantity	100

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JAN 2025

(247)

Candidate List Declared Against: JAN 2025

(247)

SVHC > Threshold:

Pb (2.02% in 30855580807)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought














TE Part #5-103168-7 18 MODII HDR DRST SHRD .100CL



TE Part #1744428-2 3.96 EP HDR ASSY 2P R/A, GW



TE Part #CONSMA001-SMD-G-T SMA Jack 50 Ohm PCB Surface Mount





Documents

Product Drawings

8P,3.81MM,SIDE ENTRY,HIGH TMP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1776113-8_0.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1776113-8_0.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1776113-8_0.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Eurostyle Terminal Blocks Focus Product Stock List

English

1-1773458-1_EURO_STYLE_TERMINAL_BLOCKS_QRG

English

Product Specifications

Application Specification

English

8 Position PCB Terminal Block, Header, Wire-to-Board, 3.81 mm [.15 in] Centerline, 1 Row, 90° Wire Entry Angle, 28 – 16 AWG, .08 – 1.4 mm² Wire



Agency Approvals

UL

English