



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **4 – 6.63 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Electrical Characteristics

Voltage Rating	250 V
----------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp



Barrel Type

Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	19 mm[.748 in]
Compatible Insulation Diameter Range	3.4 – 5.1 mm[.134 – .2 in]
Terminal Material Thickness	.33 mm[.013 in]
Wire Size	4 – 6.63 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	3000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150371-1
OCEAN_2.0_Applicator-E-160F210F-REM

KIT
TE Part # 7-2150371-7
OCEAN_2.0_SPARE_PART_KIT-160F210F

TE Part # 282178-1
FF 250 REC 0.3-0.8MM2 BR

TE Part # 1-1579007-4
EXTRACTION TOOL

TE Part # 4-1579007-3
EXTRACTION TOOL KIT

TE Part # 2150371-2
OCEAN_2.0_Applicator-E-160F210F-REA

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(195)

Insertion & Extraction Tools(2)

Quick Disconnects(216)

Customers Also Bought



TE Part #926899-3
UNIV-MNL SPLIT ST

TE Part #163300-8
MATENLOK SOCKET

TE Part #42899-2
RING TONGUE 10-6 AWG TPBR

TE Part #4-745130-0
SHLDING FERRULE,PLTD,BULK PKG

TE Part #2292802-2
AS16,PLUG BACKSHELL KIT,ST,12P, NC20

TE Part #953697-3
3POS MQS REC

TE Part #3-1394766-2
2.8FLA-STE-GEH 2X9P

TE Part #6-745129-9
SHLDING FERRULE,PLTD,BULK PKG

TE Part #DRC12-70PD
REC, 70P, BLK, N, FLANGE, D

TE Part #1102896-1
HEE.32.BU.C.B1-32

Documents

Product Drawings
FF 250 REC 4-6MM2 PTBR

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_180351-8_AF_c-180351-8-af.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_180351-8_AF_c-180351-8-af.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_180351-8_AF_c-180351-8-af.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

English