TE Internal #: 1811027-1

Tap Splice, 12 AWG, 3 Splice Capacity, Strain Relief, Copper Alloy, Brown, 24.5 mm [.965 in] Length, Loose Piece, Solid / Stranded


Wire, Copper Wire

View on TE.com >



Terminals & Splices > Splices











Splice Type: Tap Splice

Wire Size: 12 AWG

Sealable: No

Splice Capacity: 3

Splice Features: Strain Relief

### **Features**

### Product Type Features

Splice Type	Tap Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Configuration Features	
Splice Capacity	3
Compatible With Wire & Cable Type	Discrete Wire
Electrical Characteristics	
Operating Voltage	600 VDC
Body Features	
Splice Features	Strain Relief
Primary Product Color	Brown
Contact Features	

9 μm[354.33 μin]

Bright Tin

Terminal Plating Thickness

Terminal Plating Material



Contact Base Material	Copper Alloy
Mechanical Attachment	
Wire Insulation Support	Without
Housing Features	
Housing Material	Polypropylene
Dimensions	
Wire Size	12 AWG
Compatible Insulation Diameter Range	3.8 mm
Product Length	24.5 mm[.965 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Compatible With Agency/Standards Products	CSA, UL
UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	CSA C22.2 No. 188, UL 486C
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	500
Packaging Method	Loose Piece

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU ELV Directive 2000/53/EC  China RoHS 2 Directive MIIT Order No 32, 2016  No Restricted Materials Above Threshold  EU REACH Regulation (EC) No. 1907/2006  Current ECHA Candidate List: JAN 2025 (247)  Candidate List Declared Against: JUNE 2023 (235)  Does not contain REACH SVHC	EU RoHS Directive 2011/65/EU	Compliant
EU REACH Regulation (EC) No. 1907/2006  Current ECHA Candidate List: JAN 2025 (247)  Candidate List Declared Against: JUNE 2023 (235)	EU ELV Directive 2000/53/EC	Compliant
(247) Candidate List Declared Against: JUNE 2023 (235)	China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
	EU REACH Regulation (EC) No. 1907/2006	(247) Candidate List Declared Against: JUNE 2023 (235)



Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts





# Customers Also Bought























### **Documents**

### **Product Drawings**

ASSEMBLY,12AWG TAP

English

### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_1811027-1\_A1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_1811027-1\_A1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1811027-1\_A1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1811027-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1811027-1\_B.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1811027-1\_B.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

Poke-in Wire tap IDC Splice flyer

Poke-in Wire tap IDC Splice flyer

English

**Product Specifications** 

Tap Splice, 12 AWG, 3 Splice Capacity, Strain Relief, Copper Alloy, Brown, 24.5 mm [. 965 in] Length, Loose Piece, Solid / Stranded Wire, Copper Wire



**Application Specification** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English

Agency Approvals

Agency Approval Document

English