1892711-1 ✓ ACTIVE

MINIPAK

TE Internal #: 1892711-1

PCB Mount Header, Right Angle, Board-to-Board, 6 Position, 3 mm [.118 in] Centerline, Fully Shrouded, Gold (Au), Through Hole -

Press-Fit, Power

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: PCB Mount Header

PCB Mount Orientation: Right Angle
Connector System: Board-to-Board

Number of Positions: 6
Number of Rows: 2

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly
Configuration Features	
Number of Loaded Positions	6
Number of Power Positions	6
PCB Mount Orientation	Right Angle
Number of Positions	6
Number of Rows	2
Electrical Characteristics	

250 VDC

Black

Contact Features

Body Features

Operating Voltage

Primary Product Color



Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
PCB Contact Termination Area Plating Material Thickness	.5 μm[19.68 μin]
Contact Layout	Matrix
Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Blade
Contact Current Rating (Max)	18 A
Termination Features	
Termination Post & Tail Length	2.83 mm[.11 in]
Termination Method to PCB	Through Hole - Press-Fit
Mechanical Attachment	
Mating Alignment Type	Polarization
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Mating Alignment	With
Housing Features	
Housing Material	Polyester
Centerline (Pitch)	3 mm[.118 in]
Dimensions	
Row-to-Row Spacing	11.5 mm[.453 in]
Connector Width	12 mm[.47 in]
Connector Height	21.44 mm[.84 in]
Connector Length	32.35 mm[1.27 in]
Usage Conditions	
Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power



Industry Standards

Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	41
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Customers Also Bought



TE Part #2180850-7 IMP,PWR,3PR,HDR,L-HLD,2X,797-3,797-6



TE Part #1-2324171-0 CAGE ASSEMBLY, QSFP-DD 1X1, SPRING



TE Part #2-2170703-6 CAGE ASSEMBLY, QSFP28 1X1, SPRING



TE Part #1-5406552-7
INV MJ,1X4,PNL GRD,LED (-/G) W



TE Part #2057419-3 IMP100S,H,V2P10C,LG,OEW39,5.5



TE Part #2227104-1 1X2 CAGE ASSY, BHND BEZEL, QSFP28



TE Part #5223961-8 UNV,PWR,MDL.HDR,R-PEGS



TE Part #2187308-1
Tin Man Recept Assy 4 Pair 16 Column



TE Part #6-1761613-5 STEP-Z RCPT 15MM 104P LF ST

TE Part #2304921-3
ZSFP+ 1X8 CAGE ASSEMBLY, PRESS-FIT

Documents

Product Drawings

Assy 2x3 MINIPAK HDE seq1

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1892711-1_A_c-1892711-1-a.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_1892711-1_A_c-1892711-1-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1892711-1_A_c-1892711-1-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Application Specification

English