#### PIDG

TE Internal #: 1958193-1

Pin, .99 mm [.039 in] Tab Thickness, 2.6 mm [.1 in] Pin Diameter, 12

- 10 AWG, 3 - 6  $mm^2$  Wire, 5180 - 13100 CMA, Closed Barrel, Tin

Plating, PIDG

View on TE.com >



Terminals & Splices > Crimp Wire Pins, Tabs & Ferrules











Crimp Wire Terminal Type: Pin

Mating Tab Thickness: .99 mm [ .039 in ]

Mating Pin Diameter: 2.6 mm [ .1 in ]

Compatible Insulation Diameter Range: 6.4 mm, 3.81 – 6.35 mm [ .25 in, .15 – .25 in ]

Wire Size: 12 – 10 AWG

### **Features**

### **Product Type Features**

Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support

### **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire	

### **Body Features**

Sleeve Plating Material	Tin
Sleeve Material	Copper
Primary Product Color	Natural
Insulation Material	PVF2

#### **Contact Features**

Contact Mating Area Length	9.9 mm[.39 in]
Contact Fabrication	Stamped & Formed
Crimp Wire Terminal Type	Pin



Mating Tab Thickness	.99 mm[.039 in]
Mating Pin Diameter	2.6 mm[.1 in]
Barrel Type	Closed
Terminal Plating Material	Tin
Contact Shape & Form	Round
Terminal Orientation	Straight
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Compatible Insulation Diameter Range	6.4 mm, 3.81 – 6.35 mm[.25 in][.15 – .25 in]
Wire Size	5180 – 13100 CMA
Barrel Inside Diameter	6.43 mm[.253 in]
Terminal Material Thickness	.79 mm[.03 in]
Overall Product Length	29.16 mm[1.15 in]
Usage Conditions	
Insulation Option	Partially Insulated
Packaging Features	
Packaging Quantity	500
Packaging Method	Loose Piece

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts























Also in the Series | PIDG





Compression Connectors(17)



Crimp Wire Pins, Tabs & Ferrules(41)




Hand Crimping Tools(2)



Knife Disconnects(11)



Ring Terminals(588)



Spade Terminals(228)



Special Purpose Terminals(1)



Splices(41)

# Customers Also Bought





## **Documents**

Product Drawings
PIDG 12-10 PVF2 WIRE PIN

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1958193-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1958193-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1958193-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Pin, .99 mm [.039 in] Tab Thickness, 2.6 mm [.1 in] Pin Diameter, 12 – 10 AWG, 3 – 6 mm² Wire, 5180 – 13100 CMA, Closed Barrel, Tin Plating, PIDG

