TE Internal #: 1982633-1

Board-to-Board, 3 Position, 3 mm [.118 in] Centerline, Plug, 15

VDC, Right Angle, Printed Circuit Board, Signal, Board Mount, DC

Jack Connectors

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors











Connector System: Board-to-Board

Number of Positions: 3

Centerline (Pitch): 3 mm [.118 in]
Connector & Housing Type: Plug
Operating Voltage: 15 VDC

Features

Product Type Features

Connector System	Board-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	3
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	15 VDC
Body Features	
Primary Product Color	Black
Contact Features	
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	3 A

Mechanical Attachment



PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	LCP
Centerline (Pitch)	3 mm[.118 in]
Usage Conditions	
Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]
Operation/Application	
Operation/Application Circuit Application	Signal
	Signal
Circuit Application	Signal UL 94V-0
Circuit Application Industry Standards	
Circuit Application Industry Standards UL Flammability Rating	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



TE Part #2369317-1 16G 05FH 8H plug aassy 440POS 8u" Au



TE Part #CAT-R21-73106549 Bulbous Heat Shrink Boots: Lipped, Right Angle



TE Part #280755-2 FF 375 REC 6-10MM2 TPBR





TE Part #5-1437624-0
PKES60B1/4=KNOB PLSTC FLUTED W



TE Part #1747786-1
PACKING,REC. ASSY. 8POS. 2MM
PITCH BATTE



TE Part #292448-1
3.0mm PITCH 3P SMT ASSEMBLY
BATTERY CONN





Documents

Product Drawings
BATTERY CONN 3 POSITION

Board-to-Board, 3 Position, 3 mm [.118 in] Centerline, Plug, 15 VDC, Right Angle, Printed Circuit Board, Signal, Board Mount, DC Jack Connectors



English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1982633-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1982633-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1982633-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.