




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Block Function: **Disconnect**

Primary Product Color: **Gray**

Product Spacing: **5.2 mm [.205 in]**

Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	A3-B3
Number of Circuits	1
Block Function	Disconnect
Number of Positions	2

Electrical Characteristics

Power Loss	.8 W
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	150 V
Impulse Withstanding Voltage Rating (IEC)	6000 V
Current Rating (IEC)	25 A
Current Rating (UL)	25 A
Dielectric Withstanding Voltage (Max)	1890 V



Voltage Rating (IEC)	400 V
Voltage Rating (CSA)	150 V
Short-Time Withstanding Current Rating @ 1s	480 A
Operating Voltage	150 VAC

Body Features

Product Weight	8.6 g[.339 oz]
Primary Product Color	Gray

Termination Features

Termination Method to Wire & Cable	Screw Terminal
------------------------------------	----------------

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Terminal Block Disconnect Type	Blade
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	51.4 mm[2.024 in]
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	10.5 mm[.413 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	24 – 16 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	24 – 16 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	24 – 16 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.22 – 4 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	.22 – 2.5 mm²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	24 – 10 AWG
Product Length	51.35 mm[2.02 in]
Product Height	53 mm[2.087 in]
Product Spacing	5.2 mm[.205 in]
Wire Size	10 AWG

Usage Conditions



Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1SNA164800R0300
PR3.G2

TE Part # 1SNK900624R0000
KCO

TE Part # 1SNA168700R2200
PR5

TE Part # 1SNK900600R0000
SHBS

TE Part # 1SNK900606R0000
LH-J

TE Part # 1SNK149999R0000
MC512PA

TE Part # 1SNA113542R1000
PC5-2

TE Part # 1SNK900001R0000
BAM4

TE Part # 1SNK900609R0000
PROCAP5

TE Part # 1SNA168500R1200
PR4

TE Part # 1SNK140000R0000
MC512

TE Part # 1SNA113544R1200
PC5-10

TE Part # 1SNA174300R1700
PR3.Z2

TE Part # 1SNK140004R0000
MC512-YL

TE Part # 1SNK505910R0000
ES4

TE Part # 1SNK900618R0000
PL5


TE Part # 1SNK900002R0000
BAZ1

TE Part # 1SNK900604R0000
CO

TE Part # 1SNK900103R0000
CS-R1

TE Part # 1SNK900611R0000
UMH


Also in the Series | **ENTRELEC SNK**



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought



TE Part #1SNK508150R0000
ZS10-PE



TE Part #1SNK510020R0000
ZS16-BL




TE Part #1SNK508423R0000
ZS4-D2-SF1-R1



TE Part #1SNK510150R0000
ZS16-PE



TE Part #1SET411023R0000
WD-1-DP-GR8080



TE Part #1SNK506410R0000
ZS4-SF



TE Part #1SNK505010R0000
ZS4



TE Part #1SNK510010R0000
ZS16



TE Part #1SNK506150R0000
ZS6-PE



TE Part #1SNK506010R0000
ZS6

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK505310R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK505310R0000_A.3d_igs.zip

1SNK505310R0000

Screw Clamp Terminal Block, Disconnect, Gray, 5.2 mm [.205 in] Spacing, 2 Position,
Screw Terminal, Power & Signal, DIN Rail, 150 VAC, ENTRELEC SNK



English

Customer View Model

[ENG_CVM_CVM_1SNK505310R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ZS4-S](#)

English

[ENTRELEC Terminal Block - Master Catalog](#)

[ENTRELEC Terminal Block - Master Catalog](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)

[Essential Entrelec Terminal Blocks](#)

French

[Essential Entrelec Terminal Blocks](#)

English

[Essential Entrelec Terminal Blocks](#)

Japanese