



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Modular Terminal Block Product Type: **PI-Spring Terminal Block**

Block Function: **Ground**

Primary Product Color: **Green & Yellow**

Product Spacing: **12 mm [.472 in]**

Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	PI-Spring Terminal Block
-------------------------------------	--------------------------

Configuration Features

Number of Levels	1
Gauge Type	A7 & 6.3 mm Dia.
Number of Circuits	1
Block Function	Ground
Number of Positions	2

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Dielectric Withstanding Voltage (Max)	2200 V
Short-Time Withstanding Current Rating @ 1s	1920 A

Body Features

Product Weight	47 g[1.85 oz]
Primary Product Color	Green & Yellow

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail



Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	47.6 mm
Tool Size	4 mm[.157 in]
Wire Stripping Length	15 mm[.591 in]
Main Circuit Capacity - Twin Ferrule per Spring Clamp	20 – 10 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	20 – 4 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	20 – 6 AWG
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	20 – 6 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 16 mm²
Product Length	47.6 mm
Product Height	89 mm
Product Spacing	12 mm[.472 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free






Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1SNK149999R0000 MC512PA	 TE Part # 1SNK160000R0000 MC812	 TE Part # 1SNK900001R0000 BAM4	 TE Part # 1SNK900609R0000 PROCAP5
 TE Part # 1SNK900612R0000 PROCAP6	 TE Part # 1SNA168500R1200 PR4	 TE Part # 1SNK900613R0000 PROCAP8	 TE Part # 1SNK150000R0000 MC612
 TE Part # 1SNK900102R0000 BAZH1	 TE Part # 1SNA164800R0300 PR3.G2	 TE Part # 1SNK160004R0000 MC812-YL	 TE Part # 1SNK169999R0000 MC812PA



Also in the Series | ENTRELEC SNK



Customers Also Bought





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK712150R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK712150R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK712150R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ZK16-PE

English

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Essential Entrelec Terminal Blocks

Japanese

Agency Approvals

Bureau Veritas Marine and Offshore Certificate

English

1SNK712150R0000

PI-Spring Terminal Block, Ground, Green & Yellow, 12 mm [.472 in] Spacing, 2
Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK

