V23101D 103A201 ✓ ACTIVE



Axicom | Axicom W11 Relay V23101

TE Internal #: 2-1393779-6


Reed Relay, DC, Monostable, 1 Form C SPDT-CO, 1.25 A Contact Rating, 12 VAC Coil Voltage, 5 VDC Coil Voltage, Axicom W11

Relay V23101

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: Reed Relay

Current Type: DC

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form C SPDT-CO

Contact Current Rating: 1.25 A

Features

Product Type Features

Relay & Contactor Type	Reed Relay
Configuration Features	
Relay Options	Power Switching
Contact Number of Poles	1
Contact Arrangement	1 Form C SPDT-CO
Electrical Characteristics	
Contact Limiting Short-Time Current	1.25 A
Contact Limiting Making Current	1.25 A
Contact Limiting Continuous Current	1.25 A
Contact Limiting Breaking Current	1.25 A
Insulation Initial Dielectric Between Open Contacts	750 Vrms
Contact Switching Voltage (Max)	125 VAC
Contact Switching Load (Min)	10mA @ .02V
Coil Resistance	120 Ω
Insulation Initial Resistance	1000 ΜΩ
Contact Current Rating	1.25 A
Coil Voltage Rating	5 VDC
Contact Voltage Rating	120 VDC



Coil Power Rating DC	.208 W
Insulation Initial Dielectric Between Contacts & Coil	1000 Vrms
Body Features	
Product Weight	4 g[.141 oz]
Enclosure Type	Flux Resistant Automatic Solder Capable & Washable
Contact Features	
Contact Plating Material	Gold
Contact Material	Silver Palladium (AgPd) Alloy
Termination Features	
Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins
Mechanical Attachment	
Product Mount Type	Board Mount
Dimensions	
Product Width	10 mm[.393 in]
Product Length	15.4 mm[.606 in]
Product Height	11.5 mm[.452 in]
Usage Conditions	
Operating Temperature Range	-40 – 85 °C
Environmental Category of Protection	RTIII
Environmental Ambient Temperature (Max)	85 °C[85 °F]
Operation/Application	
Solder Process	Wave Solder Capable
Performance Type	Sensitive
Current Type	DC
Coil Magnetic System	Monostable
Packaging Features	
Packaging Method	Box & Tube, Tube
Other	
Coil Power Rating Class	.2 – .3 W
Contact Current Class	0 – 2 A



Environmental Ambient Temperature Class	70 – 85 °C
Height Class (Mechanical)	11 – 12 mm
Length Class (Mechanical)	14 – 16 mm
Width Class (Mechanical)	10 – 12 mm

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | Axicom W11 Relay V23101





Customers Also Bought





















Documents

CAD Files

Customer View Model ENG_CVM_CVM_2-1393779-6_B1.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_2-1393779-6_B1.3d_stp.zip

English

Reed Relay, DC, Monostable, 1 Form C SPDT-CO, 1.25 A Contact Rating, 12 VAC Coil Voltage, 5 VDC Coil Voltage, Axicom W11 Relay V23101



Customer View Model

ENG_CVM_CVM_2-1393779-6_B1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Definitions General Purpose Relays

English