



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **Time Delay Relay**

Current Type: **AC & DC**

Contact Arrangement: **2 Form C DPDT-CO**

Contact Current Rating: **5 A**

Product Mount Type: **Socket Mount**

Features

Product Type Features

Relay & Contactor Type	Time Delay Relay
------------------------	------------------

Configuration Features

Contact Arrangement	2 Form C DPDT-CO
---------------------	------------------

Electrical Characteristics

Input Voltage	120 VAC
Contact Current Rating	5 A

Mechanical Attachment

Product Mount Type	Socket Mount
--------------------	--------------

Dimensions

Product Width	50 mm[1.97 in]
Product Length	50 mm[1.97 in]
Product Height	83 mm[3.25 in]

Usage Conditions

Operating Temperature Range	-30 – 65 °C
Environmental Ambient Temperature (Max)	65 °C[149 °F]

Operation/Application

Type of Control	Knob
-----------------	------



Timing Range (Off-Time)	.5 – 15 seconds
Mode of Operation	Off-Delay
Repeatability (Max)	±1%
Current Type	AC & DC

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1437463-5
SCERW21ACA=RELAY 120VAC 1-30 S



TE Part # 1755052-3
SCERW22ABA=RLY,TRUOFF,120V,15S, 10A



TE Part # 1437463-6
SCERW21AEA=120V &125VDC 4 TO12



TE Part # 1437463-4
SCERW21ABA=120V &125VDC 0.5 TO

SCERX22ABA

Time Delay Relay, AC & DC, 2 Form C DPDT-CO, 5 A Contact Rating, Socket Mount, 65 °C [149 °F]





TE Part # 2-1437463-4
SCERX22ACA=120V&125VDC 1 TO 30



TE Part # 2-1437463-8
SCERX22AGA=120V &125VDC 10 TO3



TE Part # 3-1437463-8
SCERX22FBA=SCERX22FBA

Customers Also Bought



TE Part #207019-1
METRIMATE PLUG,36 POS



TE Part #1472958-1
SCERX22AEA=RLY,TRU OFF,120VAC/




TE Part #1SNA114836R0000
BAMH



TE Part #1SNA115501R1200
M6/8.D2



TE Part #1SNA116900R2700
BADH



TE Part #1SNA400195R2200
M35/16



TE Part #8-34567-1
TERMINAL,SOLIS R 16-14HD 10



TE Part #1SNA115261R2000
M10/10.1



TE Part #1SNA116656R2500
FEM8D1



TE Part #1SNS320001Z3271
RC810 CUSTOM PRINTED MARKERS

Documents

Product Drawings

SCERX22ABA=120V &125VDC 0.5 TO

English

Datasheets & Catalog Pages

5-1773450-5_sec12_SCE

English