

CII | CII 3SBC Relay

TE Internal #: 2-1617072-7


General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 2 A Contact Rating, 26.5 VDC Coil Voltage, CII

3SBC Relay

View on TE.com >



Relays & Contactors > Electromechanical Relays > DPDT Relay : Electrically-Held, 1/5-Size Relay



Relay & Contactor Type: General Purpose Signal Relay

Current Type: DC

Coil Magnetic System: Non-Polarized, Monostable

Contact Arrangement: 2 Form C DPDT-CO

Contact Current Rating: 2A

All DPDT Relay: Electrically-Held, 1/5-Size Relay (84)

Features

Product Type Features	
Relay & Contactor Type	General Purpose Signal Relay
Configuration Features	
Contact Arrangement	2 Form C DPDT-CO
Electrical Characteristics	
Coil Resistance	1350 Ω
Contact Current Rating	2 A
Coil Voltage Rating	26.5 VDC
Coil Power Rating DC	.52 W
Body Features	
Enclosure Type	Hermetically Sealed
Termination Features	
Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins
Mechanical Attachment	

Board Mount

Product Mount Type



Usage Conditions

Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Vibration Resistance	30G's, 10 – 3000Hz
Shock Resistance	75G's, 6ms
Current Type	DC

Non-Polarized, Monostable

Product Compliance

Coil Magnetic System

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (90% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-3SBH-4PDT-WOCS 4PDT Signal Relay: Electrically-Held, 1 /5-Size Relay



TE Part # 3-1617076-1 3SBH1262A2 = M39016/54-012M

Also in the Series | CII 3SBC Relay





Electromechanical Relays(42)



General Purpose Signal Relays(42)

Customers Also Bought



TE Part #5748979-1 AMP III RCPT 9P RA 318 FFSCRLK /BDLK



TE Part #1-207120-1 METRIMATE PIN HDR ASY,12P LF



TE Part #1-206763-4
METRIMATE PIN HDR ASSY,24P LF



TE Part #5406508-4
INV MJ,1X1,LED (Y/G)ZIF



TE Part #1-1393210-2 T9AS1D12-110



TE Part #1-207532-0 SKT HDR ASSY,24P,MMATE LF



TE Part #CAT-AM74-UN384H
AMP-LATCH UNIVERSAL HEADERS



TE Part #1-534267-2 30 MODIV VRT DR OE 100/125





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1617072-7_G_c-2-1617072-7-g.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1617072-7_G_c-2-1617072-7-g.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1617072-7_G_c-2-1617072-7-g.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773450-5_sec1_3SBC

English

RELAY

English