

### CGS | CGS SQ

TE Internal #: 2-1623779-0


47 ohm, Through-Hole Power Resistor, Wire Wound, 20 W, 5 %, ±300 ppm/°C, Radial-Leaded, Copper Termination, 60 x 14 x 13.5

mm, CGS SQ

View on TE.com >



Passive Components > Resistors > Through-Hole Resistors > Wirewound Resistor: Vertical Mount



Resistance Value:  $47 \Omega$ 

Resistor Type: Power Resistor Element Type: Wire Wound

Power Rating: 20 W

Resistance Class: Up to  $1k\Omega$ 

All Wirewound Resistor: Vertical Mount (202)

### **Features**

### Product Type Features

Number of Terminations

Passive Component Dimensions

**Dimensions** 

Product Type Features	
Resistor Type	Power Resistor
Element Type	Wire Wound
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Resistance Value	47 Ω
Power Rating	20 W
Resistance Class	Up to $1k\Omega$
Passive Component Tolerance	5 %
Body Features	
Lead Type	Radial-Leaded
Termination Features	
Termination Area Base Material	Copper

2

60 x 14 x 13.5 mm



### **Usage Conditions**

Operating Temperature Range	-55 – 250 °C
Temperature Coefficient	±300 ppm/°C
Packaging Features	
Packaging Method	Loose Piece - Box

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts






## Also in the Series | CGS SQ




# Customers Also Bought



150pc



TE Part #2-1879068-2 SQB40 47R 5% (WIRE) 6.35MM **FASTON** 




TE Part #1-2176526-8 3503G 2B 76R8 1% 5K RL











## **Documents**

**Product Drawings** SQB20 47R 5% (WIRE)

English

Datasheets & Catalog Pages 4-1773460-6\_RESISTIVE\_SOLUTIONS\_RAIL

English

47 ohm, Through-Hole Power Resistor, Wire Wound, 20 W, 5 %,  $\pm$ 300 ppm/°C, Radial-Leaded, Copper Termination, 60 x 14 x 13.5 mm, CGS SQ



### 1309350\_PASSIVE\_COMPONENT

English

8-1773459-4\_POWER\_FILTERING\_AND\_RESISTIVE\_SOLUTIONS\_FOR\_ELEVATORS\_AND\_ESCALATORS

English