



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-0**

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without

Mechanical Attachment

--



Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Length	24.7 mm[.97 in]
----------------	-----------------

Usage Conditions

Operating Temperature Range	-25 – 170 °C[-13 – 338 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	7500
--------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-1644125-4
SLEEVE EPRING 250 PA DARK GRY



TE Part # 9-1644125-4
ESPRING SLEEVE 250 HIGH TEMP NYLON BLK



TE Part # 2-1644125-3
SLEEVE ESPRING 250 NYLON DARK GRY

Also in the Series | FASTON 250



Compression Connectors(4)




Crimp Terminal Housings(116)



Insertion & Extraction Tools(6)



Insulation Boots & Sleeves(16)



Magnet Wire Terminals(1)



PCB Terminals(134)




Quick Disconnects(421)



Splices(4)


Customers Also Bought




TE Part #1-282003-6
AMP MONO-SHAPE TAB CONN



TE Part #176281-1
UNIV POWER CAP HSG 1P F/H



TE Part #336076-3
250 FASTON,E-SPRING REC.,17-14 AWG,PTBR



TE Part #1-293003-5
MONO SHAPE TAB CONNECTOR 5 POS



TE Part #2178301-1
250 FASTON, F-SPR REC., 20-18 AWG, PNST




TE Part #63854-2
250 PL MKIII REC. 18-14AWG TPBR



TE Part #63933-2
250 PL MKIII REC. 22-18AWG TPBR



TE Part #293207-3
DUOPLUG Std conn., 3 pos, gwt750 v0



TE Part #5101310001
RPS-2.5K-18-12/2.0-S3-9



TE Part #7-456135-2
CRIMPER, INSULATION "O"(.155")

Documents

Product Drawings

E SPRING .250 (6.3 MM) RECEPTACLE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1644125-8_E_c-2-1644125-8-e.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1644125-8_E_c-2-1644125-8-e.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1644125-8_E_c-2-1644125-8-e.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

E-Spring Flyer

English

Product Specifications

6,35 E-SPRING CONTACT RECEPTACLES SLEEVES

English

Application Specification

English

2-1644125-8

Receptacle, Receptacle, 1 Position, Straight, UL 94V-0, Natural, Polyamide, Cable Mount (Free-Hanging), FASTON 250, Crimp Terminal Housings

