



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **High Voltage Relay**

Current Type: **DC**

Coil Magnetic System: **Monostable**

Contact Arrangement: **1 Form X SPST-NO-DM**

Coil Voltage Rating: **12 VDC**

Features

Product Type Features

Relay & Contactor Type	High Voltage Relay
------------------------	--------------------

Configuration Features

Coil Special Features	Without Resistor in Parallel
Contact Arrangement	1 Form X SPST-NO-DM

Electrical Characteristics

Contact Limiting Making Current	20 A
Coil Resistance	50 Ω
Contact Limiting Breaking Current	20 A
Insulation Initial Dielectric Between Open Contacts	2000 Vrms
Contact Switching Voltage (Max)	450 VDC
Coil Voltage Rating	12 VDC
Contact Voltage Rating	400 VDC
Coil Power Rating DC	2.9 W
Insulation Initial Dielectric Between Contacts & Coil	2000 Vrms

Body Features

Product Weight	17 g[.6 oz]
Enclosure Type	Flux Resistant Automatic Solder Capable & Washable



Contact Features

Contact Material	Silver Alloy
------------------	--------------

Termination Features

Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins

Mechanical Attachment

Product Mount Type	Board Mount
--------------------	-------------

Dimensions

Product Width	20.7 mm[.815 in]
Product Length	25.55 mm[1.006 in]
Product Height	19.3 mm[.76 in]

Usage Conditions

Environmental Category of Protection	RTIII
Environmental Ambient Temperature (Max)	85 °C[185 °F]

Operation/Application

Solder Process	Wave Solder Capable
Current Type	DC
Coil Magnetic System	Monostable

Other

Contact Current Class	<20 A
Environmental Ambient Temperature Class	-40 – 85 °C
Height Class (Mechanical)	16 – 20 mm
Length Class (Mechanical)	25 – 30 mm
Width Class (Mechanical)	20 – 25 mm

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JUNE 2023 (235)
Does not contain REACH SVHC

Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2-1904058-7
[V23700F0002A408-EV-CBOX](#)

Also in the Series | Mini K HV Precharge Relay


Automotive Relays(2)

High Voltage Relays(2)

PCB Relays(1)

Plug-In Relays(1)

Customers Also Bought



TE Part #1379030-3
12pos MQS .63 header 90deg



TE Part #1-179277-5
DYNAMIC 3200 HDR ASSY 4P H




TE Part #CAT-AC853-T273
PRESS FIT PIN TERMINALS




TE Part #1802824-4
8POS,TAB0.63X0.63,HDR ASSY,
90DEG,COD 1



TE Part #1802824-6
8POS,TAB0.63X0.63,HDR ASSY,
90DEG,COD 3




TE Part #2-2333210-6
1POS,FAKRA AUT,HDR ASSY,180DEG,
COD F



TE Part #5-1393472-1
V23540B3606Z 11=6P. EINREIHIGE



TE Part #2312311-2
V23717A0001A200-SZ-CBOX



TE Part #538098-3
SCHNITTSTELLE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1904058-5_A_c-2-1904058-5-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1904058-5_A_c-2-1904058-5-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1904058-5_A_c-2-1904058-5-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

High Voltage Relays & Contactors, High Voltage Relay, Mini K HV Precharge Relay

English



Product Specifications

Definitions General Purpose Relays

English