




MQS

TE Internal #: 2-2138650-1
2 Position Housing, Housing for Female Terminals, Wire-to-Board /
Wire-to-Device, 2.54 mm [.1 in] Centerline, Natural, Signal
[View on TE.com >](#)

Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Number of Positions: 2
Connector & Housing Type: **Housing for Female Terminals**
Mating Tab Width: .63 mm [.025 in]
Connector System: **Wire-to-Board, Wire-to-Device**
Centerline (Pitch): 2.54 mm [.1 in]

[All MQS, CONNECTOR HOUSING \(338\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	2
Number of Rows	1

Body Features

Cable Exit Angle	180°
Primary Product Color	Natural
Connector & Keying Code	B



Contact Features

Contact Size	.63mm
Contact Type	Receptacle
Mating Tab Width	.63 mm[.025 in]

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Product Width	16.5 mm[.65 in]
Product Length	6.8 mm[.268 in]
Connector Height	10.68 mm[.42 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Method	Box
Packaging Quantity	6000

Other

Serviceable	No
Connector Position Assurance Capable	No



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



TE Part #1241634-3
4POS MQS REC COD C



TE Part #829131P012
ES2000-NO.1-C1-0-50MM



TE Part #2-1633738-0
CRIMPER, WIRE F .063



TE Part #316833-2
040 SEALED REC CONT S FORMING



TE Part #1612121-5
SQUIB 2POS PLUG HSG



TE Part #1612123-1
SQUIB FERRITE



TE Part #6-1633964-6
CRIMPER, INSULATION OV PREMIUM



TE Part #5-2138650-1
2POS MQS REC COD E

TE Part #2475845-1
4 POS. TAB ASSY AMP SUPERSEAL
1.5 SRS

TE Part #2475841-1
4 POS. PLUG ASSY AMP SUPERSEAL
1.5 SRS

Documents

Product Drawings

2POS MQS REC COD B

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-2138650-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-2138650-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-2138650-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Product Specification

English