2-2273124-4 - ACTIVE

TE Internal #: 2-2273124-4 M8 to M12 Cable Assembly, 3 Position, 1.5 m, Sensor/Actuator, A Code, M8 Plug End A, M12 Socket End B, Double Ended, Plastic View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M8 Male Straight to Female LED Double Ended Cable



Cable Assembly Type: M8 to M12

Number of Positions: 3

Cable Assembly Length: 1.5 m

M8/M12 Application Type: Sensor/Actuator

Connector & Keying Code: A

All M8 Male Straight to Female LED Double Ended Cable (20)

Features

Product Type Features

Cable Assembly Type

Cable Assembly (End A)

M8 to M12

M8 Plug

Cable Assembly (End B)	M12 Socket
Configuration Features	
Number of Positions	3
Electrical Characteristics	
Operating Voltage	24 VDC
Body Features	
Jacket Material	PUR, PVC
Connector Color (End B)	Black
Connector Color (End A)	Black
Cable Color	Black
Wire Color (Base)	Brown, Blue, Black
Connector & Keying Code	A
Contact Features	
Contact Current Rating (Max)	4 A
Mechanical Attachment	

& For support call+1 800 522 6752

2-2273124-4

M8 to M12 Cable Assembly, 3 Position, 1.5 m, Sensor/Actuator, A Code, M8 Plug End A, M12 Socket End B, Double Ended, Plastic



Thread Size	M8 × M8
Connector Orientation (End A)	Right Angle
Connector Orientation (End B)	Straight
Housing Features	
Housing Material	Plastic
Dimensions	
Outside Cable Diameter	4.5 mm[.177 in]
Wire Size	22 AWG
Usage Conditions	
Operating Temperature Range	-30 – 80 °C[-22 – 176 °F]
Operation/Application	
Indicator Type	LED
M8/M12 Application Type	Sensor/Actuator
Shielded	No
Packaging Features	
Packaging Method	Box
Packaging Quantity	25

Packaging Quantity

Other

Field Serviceable	Yes
Cable Assembly Length	1.5 m
Cable Assembly Configuration	Double Ended

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

C For support call+1 800 522 6752

2-2273124-4

M8 to M12 Cable Assembly, 3 Position, 1.5 m, Sensor/Actuator, A Code, M8 Plug End A, M12 Socket End B, Double Ended, Plastic



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # T4051320003-004 M8 CABLE ST FEMALE 3M 3P PUR CABLE

Customers Also Bought



TE Part #1-1825058-3

ADE06S04=DIP SWTCH,EXT,SMT-GW

TE Part #CAT-C73765-M1E

M12 Field Installable Unshielded

Documents

TE Part #1-2273004-1

M8 x 1.0 straight plug Pigtail Shld

Product Drawings

C For support call+1 800 522 6752

2-2273124-4

M8 to M12 Cable Assembly, 3 Position, 1.5 m, Sensor/Actuator, A Code, M8 Plug End A, M12 Socket End B, Double Ended, Plastic



M8 angled scket to M8 strght plug 2 LED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-2273124-4_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-2273124-4_A.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_2-2273124-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications Product Specification

English