

TE Internal #: 2-2439028-1

10 A Snap Action Switch, Single Pole - Double Throw Configuration

(Pole-Throw), Short Roller, 125 VAC / 250 VAC, 220 g [7.76 oz]

Operating Force

View on TE.com >




Switches > Snap Action Switches











Contact Current Rating: 10 A

Configuration (Pole-Throw): Single Pole - Double Throw

Actuator Style: Short Roller

Operating Voltage: 125 VAC, 250 VAC
Operating Force: 220 g [7.76 oz]

Features

Product Type Features

Actuator Style	Short Roller
Switch Style	Miniature
Switch Connection Type	Quick Connect Terminal

Configuration Features

Operating Position	20.7 mm[.814 in]
Configuration (Pole-Throw)	Single Pole - Double Throw

Electrical Characteristics

Contact Current Rating	10 A
Operating Voltage	125 VAC, 250 VAC

Body Features

Releasing Force	35 g[1.234 oz]
Movement Differential	.45 mm[.017 in]
Product Orientation	Vertical

Dimensions



Pre Travel	2.7 mm[.106 in]
Operation/Application	
Operating Force	220 g[7.76 oz]
Other	
Over Travel	1.1 mm[.043 in]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

10 A Snap Action Switch, Single Pole - Double Throw Configuration (Pole-Throw), Short Roller, 125 VAC / 250 VAC, 220 g [7.76 oz] Operating Force





Documents

Product Drawings

HCP10A, Std Force, 0.187 Term. Sht Roller

English

CAD Files

Customer View Model

ENG_CVM_CVM_2-2439028-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-2439028-1_A.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2-2439028-1_A.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ALCOSWITCH_HCP_SERIES

English