




PIDG

TE Internal #: 2-320862-1  
Spade Flange Tongue Terminal, 16 – 14 AWG, #8 / M4 Stud, 4.17 mm [.164 in] Stud Diameter, Closed Barrel, Flanged, Tin Plating, PIDG

[View on TE.com >](#)

Terminals & Splices > Spade Terminals > PIDG Flanged Spade Tongue Terminals



Spade Terminal Type: **Spade Flange Tongue Terminal**  
Wire Size: **2050 – 5180 CMA**  
Stud Size: **#8, M4**

[All PIDG Flanged Spade Tongue Terminals \(51\)](#)

Features

Product Type Features

|                                        |                    |
|----------------------------------------|--------------------|
| Stud Size                              | #8, M4             |
| Sealable                               | No                 |
| Wire Insulation Support Retention Type | Insulation Support |

Electrical Characteristics

|                |       |
|----------------|-------|
| Voltage Rating | 300 V |
|----------------|-------|

Body Features

|                |       |
|----------------|-------|
| Product Weight | .97 g |
|----------------|-------|

Contact Features

|                           |                              |
|---------------------------|------------------------------|
| Spade Terminal Type       | Spade Flange Tongue Terminal |
| Barrel Type               | Closed                       |
| Terminal Orientation      | Flanged                      |
| Terminal Plating Material | Tin                          |

Mechanical Attachment

|  |  |
|--|--|
|  |  |
|--|--|



|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

Dimensions

|                                      |                               |
|--------------------------------------|-------------------------------|
| Wire Size                            | 2050 – 5180 CMA               |
| Stud Diameter                        | 4.17 mm[.164 in]              |
| Tongue Thickness                     | .79 mm[.031 in]               |
| Product Length                       | 18.72 mm[.737 in]             |
| Compatible Insulation Diameter (Max) | 4.32 mm[.17 in]               |
| Compatible Insulation Diameter Range | 2.92 – 4.31 mm[.115 – .17 in] |

Usage Conditions

|                   |                     |
|-------------------|---------------------|
| Insulation Option | Partially Insulated |
|-------------------|---------------------|

Operation/Application

|                                       |        |
|---------------------------------------|--------|
| Compatible With Wire Base Material    | Copper |
| Compatible With Wire Plating Material | Tin    |

Industry Standards

|                               |    |
|-------------------------------|----|
| Government Qualified Terminal | No |
|-------------------------------|----|

Packaging Features

|                    |              |
|--------------------|--------------|
| Packaging Quantity | 5000         |
| Packaging Method   | Tape Mounted |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2025 (247)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                  |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 59824-1  
TETRA-CRIMP PIDG PG FASTON 22-10 ASSY

TE Part # 169404  
CERTI-LOK DIE

TE Part # 58423-1  
DIE, RBY IS9252

TE Part # 47386  
DAHT PG PIDG 26-16 ASSY

TE Part # 58433-3  
PRO CR ASSY, RBY IS9252

Also in the Series | PIDG

Compression Connectors(17)


Crimp Wire Pins, Tabs & Ferrules(41)

Knife Disconnects(11)

Quick Disconnects(38)



Ring Terminals(588)



Spade Terminals(228)




Special Purpose Terminals(1)




Splices(41)


Customers Also Bought



TE Part #350547-3  
UMNL PIN 20-14 PTPPHBZ L/P




TE Part #174779-1  
PL 110 HOUSING RECEPTACLE



TE Part #2-520261-2  
ULTRA-FAST 187 ASY REC 22-18 TPBR



TE Part #40696  
RING TERMINAL 12-10 AWG TPBR




TE Part #1217113-2  
187 PL MKIII REC. 22-18AWG TPBR



TE Part #770987-1  
MINI UMNL PIN 22-18AWG SN LP



TE Part #1-480703-2  
04P UMNL CAP HSG RED



TE Part #CAT-P592-F614  
PIDG Flanged Spade Tongue Terminals



TE Part #2-34145-1  
PG R 22-16 COMM 22-18 MIL 8

Documents

Product Drawings

TERMINAL,PIDG SPD FLG 16-14 8

English

CAD Files

3D PDF

English

Customer View Model

ENG\_CVM\_2-320862-1\_J.3d\_igs.zip



English

Customer View Model

[ENG\\_CVM\\_2-320862-1\\_J.3d\\_stp.zip](#)

English

Customer View Model

[ENG\\_CVM\\_2-320862-1\\_J.2d\\_dxf.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

Agency Approvals

[UL Report](#)

English