# 2-324309-2 ACTIVE

#### **SOLISTRAND**

TE Internal #: 2-324309-2

Butt Splice, 6 AWG, 13 – 15 mm<sup>2</sup> Wire, Sight Hole, 20800 – 33100

CMA, Copper, 25.78 mm [1.015 in] Length, Loose Piece, Closed

Barrel

View on TE.com >



Terminals & Splices > Splices





=TE



Splice Type: Butt Splice
Wire Size: 13 – 15 mm²

Sealable: No

Splice Features: Sight Hole

### **Features**

### **Product Type Features**

Splice Accessory Type	Splice
Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Body Features  Product Weight	8.499 g
	8.499 g Sight Hole
Product Weight	
Product Weight  Splice Features	
Product Weight  Splice Features	Sight Hole



Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Outside Diameter	9.37 mm[.369 in]
Wire Size	20800 – 33100 CMA
Barrel Inside Diameter	5.89 mm[.232 in]
Terminal Material Thickness	1.45 mm[.057 in]
Product Length	25.78 mm[1.015 in]
Usage Conditions	
Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	

No

100

Loose Piece

# Product Compliance

**Packaging Features** 

Packaging Quantity

Packaging Method

Government Qualified Splice

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



















# Customers Also Bought





TE Part #36149 PIDG R 22-16 COMM 22-18 MIL 6



TE Part #1-967348-2 MQS KAPPE KPL 32P



TE Part #5-2301994-3 RJ45 JACK INT.MAG. 10/100 1X1 INV.





TE Part #1-331366-0 PIDG SPDFLG 22-16COM22-18MIL10



TE Part #1-2176587-3 RLC73M 2E R033 1% 1K RL



TERMINAL, SOLIS R 12-10 1/4







#### **Documents**

**Product Drawings** SPLICE, SOLIS BUTT 6

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-324309-2\_S.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-324309-2\_S.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-324309-2\_S.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Instruction Sheets** 

Butt Splice, 6 AWG, 13 – 15 mm<sup>2</sup> Wire, Sight Hole, 20800 – 33100 CMA, Copper, 25.78 mm [1.015 in] Length, Loose Piece, Closed Barrel



#### Instruction Sheet (U.S.)

English

Agency Approvals

**UL Report** 

English