




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Electrical Characteristics

Voltage Rating	600 V
----------------	-------

Body Features

Insulation Material	Nylon
---------------------	-------

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass



Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Closed

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	21.75 mm[.855 in]
Compatible Insulation Diameter Range	3.43 mm[.135 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Fully Insulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	1400
Packaging Method	Strip/Reel

Other

Barrel Color	Red
--------------	-----

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)




Candidate List Declared Against: JAN 2025 (247)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




KIT

TE Part # 7-2151034-7
[OCEAN_2.0_SPARE_PART_KIT-176O](#)



TE Part # 58628-2
[PROCRMP DIESET 26-14 ULTRAFast](#)



TE Part # 90390-3
[DIES ULTRA-FAST FASTON 22-18 DIE SET](#)



TE Part # 2151034-2
[OCEAN_2.0_APPLICATOR-S-176O-SSA](#)



TE Part # 58628-1
[PROCRIMP T&D 26-14 ULTRAFast](#)



TE Part # 58078-3
[TETRA CRIMP FRAME W/O DIES](#)

Also in the Series | [Ultra-Fast 250](#)



Automotive Housings(3)




Quick Disconnects(49)


Customers Also Bought



TE Part #880297-1
6 WAY FF 250 HOUSING REC PA 6.6
NATURAL




TE Part #640052-1
RING 18-14 AWG SST




TE Part #2-521144-2
ULTRA-FAST 250 ASY TAB 22-18 TPBR




TE Part #63854-2
250 PL MKIII REC. 18-14AWG TPBR



TE Part #2-520262-2
ULTRAFAST 187 ASSY REC 22-18
TPBR LP



TE Part #2-520979-2
ULTRA-FAST .110/.125 ASY REC 22-18
TPBR



TE Part #350436-2
RING TERMINAL 18-14 AWG TPST



TE Part #640582-1
08P UMNL PLUG HSG



TE Part #NB07112001
BATTU-20.1/8.9-A1-0-STK



TE Part #5-520263-2
ULTRA-FAST 250 ASY REC 22-18 AWG
TPBR

Documents

Product Drawings

ULTRA-FAST 250 ASSEMBLY TAB 22-18 AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-520102-1_N.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_2-520102-1_N.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-520102-1_N.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL](#)

English