#### **METRIMATE**

TE Internal #: 211759-1

Housing, Receptacle, Wire-to-Panel / Wire-to-Wire, UL 94V-0, 12 Position, 4.39 mm [.173 in] Centerline, Rectangular Wire & Cable

Connectors & Housings

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Panel, Wire-to-Wire

UL Flammability Rating: UL 94V-0

Number of Positions: 12

## **Features**

## **Product Type Features**

Compatible With Discrete Wire Type	Stranded
Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	12
Number of Rows	4
Electrical Characteristics	
Operating Voltage	600 VAC
Body Features	
Primary Product Color	Black



## **Contact Features**

Contact Type	Pin
Contact Current Rating (Max)	13 A

## Mechanical Attachment

Panel Mount Feature Type	Screw Mount
Connector Mounting Type	Panel Mount

# **Housing Features**

Housing Material	Polyester
Centerline (Pitch)	4.39 mm[.173 in]

## **Dimensions**

Connector Width	30.23 mm[1.19 in]
Row-to-Row Spacing	4.39 mm[.173 in]
Connector Height	40.77 mm[1.605 in]
Connector Length	49.33 mm[1.942 in]

# **Usage Conditions**

66 °F]
20

# Operation/Application

Circuit Application	Power & Signal

# **Industry Standards**

Compatible With Agency/Standards Products	CSA, UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0

# **Packaging Features**

Packaging Method	Package
Packaging Quantity	150

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JAN 2025

(247)

Candidate List Declared Against: JAN 2025

(247)

Does not contain REACH SVHC

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts







# **Customers Also Bought**























## **Documents**

## **Product Drawings**

**RECEPT HSG,12 POSN,METRIMATE** 

English

## **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_211759-1\_T1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_211759-1\_T1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_211759-1\_T1.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

# Datasheets & Catalog Pages

METRIMATE\_PIN\_SOCKET\_CATALOG

English

# **Product Specifications**

**Application Specification** 

English

## **Agency Approvals**

**Agency Approval Document** 

Housing, Receptacle, Wire-to-Panel / Wire-to-Wire, UL 94V-0, 12 Position, 4.39 mm [. 173 in] Centerline, Rectangular Wire & Cable Connectors & Housings



English